



DEPARTMENT OF PLANNING, BUILDING & ZONING

111 West Fox Street • Room 203

Yorkville, IL • 60560

(630) 553-4141

Fax (630) 553-4179

**Petition 22-11
Tim Raymond on Behalf of TMF Plastic Solutions, LLC
Site Plan Approval**

BACKGROUND AND INTRODUCTION

In December 2021, the Petitioner received approval to construct an approximately twenty thousand six hundred thirty (20,630) square foot addition to the north and east of the existing approximately forty-five thousand six hundred ninety-two (45,692) square foot building located on Parcel One of the subject property. The proposal also called for a stormwater pond north of the proposed addition. The addition will consist of two (2) new loading docks on the on the southeast side of the addition.

In April 2022, the Petitioner submitted a revised site plan showing a two thousand, eight hundred thirty-two (2,832) square foot addition to the southern parking lot. The proposal also increases the number of parking spaces in the southern parking lot from thirty-eight (38) to sixty-four (64), including increasing the number of handicapped accessible stalls from two (2) to three (3).

Section 13:10 of the Zoning Ordinance requires site plan review for structures on properties zoned M-1.

The property has been zoned M-1 since 1966.

The property received site plan approval for the construction of an approximately thirty-four thousand (34,000) square foot storage facility in 2008.

The revised site plan is included Attachment 1. The stormwater calculations are included as Attachment 2. WBK Engineering's comments are included as Attachment 3. The site plan that was approved in December 2021 is included as Attachment 4.

SITE INFORMATION

PETITIONER: Tim Raymond on Behalf of TMF Plastic Solutions, LLC

ADDRESS: 12127 Galena Road, Unit B

LOCATION: Approximately 0.3 Miles East of Jeter Road on the North Side of Galena Road



TOWNSHIP: Little Rock

PARCEL #: 01-01-200-002

LOT SIZE: 6.00 +/- Acres

EXISTING LAND USE: Offices and Warehouse of a Plastics Business

ZONING: M-1 Limited Manufacturing District

LRMP: Future Land Use	Rural Estate Residential (Max Density 0.45 DU/Acre)
Roads	Galena Road is County maintained Major Collector Road.
Trails	The County has a trail planned along Galena Road.
Floodplain/Wetlands	There is no floodplain on the property. There are no wetlands on the property.

REQUESTED ACTION: Site Plan Approval

APPLICABLE REGULATIONS: Section 13:10 – Site Plan Approval

SURROUNDING LAND USE

Location	Adjacent Land Use	Adjacent Zoning	Land Resource Management Plan	Zoning within 1/2 Mile
North	Single-Family Residential/Wooded	A-1 BP	Rural Estate Residential (Max Density 0.45 DU/Acre)	N/A
South	Industrial	M-1	Rural Estate Residential	N/A
East	Agricultural	A-1	Rural Estate Residential	N/A
West	Agricultural/Wooded	A-1	Rural Estate Residential	N/A

The subject property is not located within any municipal planning jurisdiction.

ACTION SUMMARY

LITTLE ROCK TOWNSHIP

Petition information was sent to Little Rock Township on May 16, 2022.

LITTLE ROCK-FOX FIRE PROTECTION DISTRICT

Petition information was sent to the Little Rock-Fox Fire Protection District on May 16, 2022.

DESIGN STANDARDS

Pursuant to Section 13:10.D of the Kendall County Zoning Ordinance, the following shall be taken into account

when reviewing Site Plans (Staff comments in bold):

*Responsive to Site Conditions-Site plans should be based on an analysis of the site. Such site analysis shall examine characteristics such as site context; geology and soils; topography; climate and ecology; existing vegetation, structures and road network; visual features; and current use of the site. In addition to the standards listed below, petitioners must also follow the regulations outlined in this Zoning Ordinance. To the fullest extent possible, improvements shall be located to preserve the natural features of the site, to avoid areas of environmental sensitivity, and to minimize negative effects and alteration of natural features. Fragile areas such as wetlands and flood plains should be preserved as open space. Slopes in excess of 20 percent as measured over a 10-foot interval also should remain as open space, unless appropriate engineering measures concerning slope stability, erosion and safety are taken. **The majority of the subject property is already an improved industrial use. The only new landscaping will be around the pond. No floodplains or wetlands are located on the property. No excessive slopes exist on the property. A stormwater management permit will be required for the pond. The Petitioners are proposing to pay a fee-in-lieu as allowed by the Kendall County Stormwater Management Ordinance.***

*Traffic and Parking Layout-Site plans should minimize dangerous traffic movements and congestion, while achieving efficient traffic flow. An appropriate number of parking spaces shall be provided while maintaining County design standards. The number of curb cuts should be minimized and normally be located as far as possible from intersections. Connections shall be provided between parking areas to allow vehicles to travel among adjacent commercial or office uses. Cross-access easements or other recordable mechanisms must be employed. **The property already possesses access off of Galena. The property presently has thirty-eight (38) parking spaces including two (2) handicapped parking space which will be increased to sixty-four (64) parking spaces including three (3) handicapped parking spaces***

*Conflicts between pedestrians and vehicular movements should be minimized. When truck traffic will be present upon the site, the road size and configuration shall be adequate to provide for off-street parking and loading facilities for large vehicles. Barrier curb should be employed for all perimeters of and islands in paved parking lots, as well as for all service drives, loading dock areas, and the equivalent. Parking lots in industrial or commercial areas shall be paved with hot-mix asphalt or concrete surfacing. **No conflicts are foreseen. The parking lot will meet applicable surfacing requirements.***

*Site Layout-Improvements shall be laid out to avoid adversely affecting ground water and aquifer recharge; minimize cut and fill; avoid unnecessary impervious cover; prevent flooding and pollution; provide adequate access to lots and sites; and mitigate adverse effects of shadow, noise, odor, traffic, drainage and utilities on neighboring properties. **Improvements are laid out to avoid adversely impacting ground water, avoid unnecessary impervious cover, prevent flooding and pollution, mitigate adverse effects of shadow, noise odor, traffic, drainage, and utilities on neighboring properties.***

*Consistent with the Land Resource Management Plan-The proposed use and the design of the site should be consistent with the Land Resource Management Plan. **This is true because the use is existing.***

*Building Materials-The proposed site plan design shall provide a desirable environment for its occupants and visitors as well as its neighbors through aesthetic use of materials, textures and colors that will remain appealing and will retain a reasonably adequate level of maintenance. Buildings shall be in scale with the ultimate development planned for the area. Monotony of design shall be avoided. Variations in detail, form, and setting shall be used to provide visual interest. Variation shall be balanced by coherence of design elements. **Not applicable as part of this amendment.***

*Relationship to Surrounding Development-A site shall be developed in harmony with neighboring street pattern, setbacks and other design elements. **The proposed pavement addition and parking layout is in harmony with the existing use.***

*Open Space and Pedestrian Circulation-Improvements shall be designed to facilitate convenient and safe pedestrian and bicycle movement within and to the property. **This is not an issue.***

Buffering-Measures shall be taken to protect adjacent properties from any undue disturbance caused by excessive noise, smoke, vapors, fumes, dusts, odors, glare or stormwater runoff. Incompatible, unsightly

activities are to be screened and buffered from public view. **Because the use is already in existence, there are no concerns regarding noise, smoke, vapors, fumes, dusts, odors or glare. The stormwater management permit will address any concerns regarding stormwater.**

Emergency Vehicle Access-Every structure shall have sufficient access for emergency vehicles. Circulation already exists in the property for emergency vehicles.

Mechanical Equipment Screening-All heating, ventilation and air conditioning equipment shall be screened on sides where they abut residential districts. Not applicable as part of this amendment.

Lighting-The height and shielding of lighting fixtures shall provide proper lighting without hazard to motorists on adjacent roadways or nuisance to adjacent residents by extending onto adjacent property. Cut-off lighting should be used in most locations, with fixtures designed so that the bulb/light source is not visible from general side view. Lighting was addressed as part of the December 2021 site plan approval.

Refuse Disposal and Recycling Storage Areas-All refuse disposal and recycling storage areas should be located in areas designed to provide adequate accessibility for service vehicles. Locations should be in areas where minimal exposure to public streets or residential districts will exist. Screening shall be required in areas which are adjacent to residential districts or are within public view. Such enclosures should not be located in landscape buffers. Refuse containers and compactor systems shall be placed on smooth surfaces of non-absorbent material such as concrete or machine-laid asphalt. A concrete pad shall be used for storing grease containers. Refuse disposal and recycling storage areas serving food establishments shall be located as far as possible from the building's doors and windows. The use of chain link fences with slats is prohibited. Not applicable as part of this amendment.

RECOMMENDATION

Pending comments from ZPAC members, Staff recommends approval of the proposed amendment to an existing site plan as proposed with the following conditions:

1. The site plan approved on December 7, 2021, shall be amended to incorporate the subject site plan (Attachment 1).
2. The site shall be developed in accordance with all applicable federal, state, and local laws related to site development and the type of use proposed for the site, including, but not limited to, securing the applicable building and stormwater permits.

ATTACHMENTS


1. Revised Site Plan
2. Stormwater Calculations
3. WBK Engineering Comments Dated May 6, 2022
4. December 8, 2021 Site Plan Approval Documents

ENGINEERING PLANS FOR TMF MANAGEMENT, LLC PARKING ADDITION

SECTION 1, TOWNSHIP 37 NORTH, RANGE 6 EAST

12127B GALENA RD
PLANO, IL 60545
KENDALL COUNTY
APRIL, 2022

LEGEND	
---	PROPERTY BOUNDARY
---600---	EXISTING CONTOUR LINE
---	EXISTING STORM SEWER
---	EXISTING SANITARY SEWER LINE
---	EXISTING WATERMAIN
---	EXISTING UNDERGROUND ELECTRIC
---	EXISTING OVERHEAD ELECTRIC
---	EXISTING GAS SERVICE
---	EXISTING TELEPHONE
---	PROPOSED CONTOUR LINE
---	PROPOSED WATERMAIN
---	PROPOSED STORM SEWER
---	PROPOSED SANITARY SEWER LINE
---	PROPOSED GREASE SERVICE LINE
---	PROPOSED VENT LINE
---	EXISTING FENCELINE
---	PROPOSED SILT FENCE
x 686.00	EXISTING SPOT SHOT
x 686.00	PROPOSED SPOT GRADE
EXIST	PROP
WATER: ○	B-BOX
○	HYDRANT
○	VALVE
○	VALVE VAULT
STORM: ▨	INLET-CURB
○	INLET OR MANHOLE
▽	FLARED END SECTION
SANITARY: ⊙	CLEANOUT
⊙	MANHOLE
⊗	R.O.W. MONUMENT
▲	PROPERTY PIN
▲	P.K. NAIL
■	CHISELED MARK
■	BENCHMARK
■	HUB & TACK
○	SOIL BORING
→	OVERLAND RELIEF
→	FLOW DIRECTION
○	UTILITY POLE
○	GUY WIRE LOC.
□	UTIL CABINET
□	UTIL PEDESTAL
○	LIGHT POLE
○	TRAFFIC SIGNAL
○	ELECTRIC VAULT
○	GAS VALVE



INDEX TO SHEETS

1. COVER SHEET
2. EXISTING CONDITIONS & DEMOLITION PLAN
3. CIVIL SITE PLANS
4. GENERAL NOTES & DETAILS



Know what's below.
Call before you dig.

Contractor and/or sub-contractors shall verify locations of all underground utilities prior to digging. Contact J.U.L.I.E. (Joint Utility Locating for Excavators) at 1-800-892-0123 or dial 811.


UTILITY STATEMENT

THE UTILITIES SHOWN HAVE BEEN LOCATED FROM VISIBLE FIELD EVIDENCE AND EXISTING DRAWINGS, MAPS AND RECORDS SUPPLIED TO SURVEYOR. THE SURVEYOR MAKES NO GUARANTEES THAT THE UTILITIES SHOWN COMPRISE ALL SUCH UTILITIES IN THE AREA, EITHER IN SERVICE OR ABANDONED. THE SURVEYOR FURTHER DOES NOT WARRANT THAT THE UTILITIES SHOWN ARE IN THE EXACT LOCATION INDICATED, ALTHOUGH THEY ARE LOCATED AS ACCURATELY AS POSSIBLE FROM AVAILABLE INFORMATION. THE SURVEYOR HAS PHYSICALLY LOCATED VISIBLE STRUCTURES; HOWEVER, HE HAS NOT PHYSICALLY LOCATED THE UNDERGROUND LINES.

PROFESSIONAL ENGINEER'S CERTIFICATION
STATE OF ILLINOIS, COUNTY OF KENDALL

I JOHN J. TEBRUGGE, A LICENSED PROFESSIONAL ENGINEER OF ILLINOIS, HEREBY CERTIFY THAT THESE PLANS HAVE BEEN PREPARED UNDER MY PERSONAL DIRECTION BASED ON AVAILABLE DOCUMENTS AND FIELD MEASUREMENTS FOR THE EXCLUSIVE USE OF THE CLIENT NOTED HEREON.

GIVEN UNDER MY HAND & SEAL THIS 26TH DAY OF APRIL, 2022



ILLINOIS REGISTERED PROFESSIONAL ENGINEER
NO. [REDACTED] EXPIRES NOV. 30, 2023

COPYRIGHT © 2021 BY TEBRUGGE ENGINEERING
ALL RIGHTS RESERVED. NO PART OF THESE CIVIL ENGINEERING PLANS MAY BE REPRODUCED, DISTRIBUTED, OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, INCLUDING PHOTOCOPYING, RECORDING, OR OTHER ELECTRONIC OR MECHANICAL METHODS, WITHOUT THE PRIOR WRITTEN PERMISSION OF TEBRUGGE ENGINEERING.

BENCHMARKS:

1. NATIONAL GEODETIC SURVEY MONUMENT PID - MF0523
LOCATED 320 FEET EAST OF THE PLANO TRAIN STATION, 21 FEET NORTH OF THE CENTERLINE OF THE NORTH TRACK, AT AN ABANDONED SIGNAL BRIDGE FOUNDATION STANDARD DISK IN CONCRETE STAMPED "Y 49 1934"
NAVD 88 DATUM
ELEVATION = 649.12
2. ON-SITE BENCHMARK NORTH EAST CORNER OF ELECTRIC TRANSFORMER PAD (LOCATION ON PLAN)
NAVD 88 DATUM
ELEVATION = 671.88

PLANS PREPARED FOR:


TMF MANAGEMENT, LLC
12127 GALENA ROAD - UNIT B
PLANO, IL 60545
PHONE: (630) 552-7575

CIVIL ENGINEER:

TEBRUGGE ENGINEERING
410 E CHURCH ST - SUITE A
SANDWICH, ILLINOIS 60548
(815) 786-0195


INFO@TEBRUGGEENGINEERING.COM
WWW.TEBRUGGEENGINEERING.COM

NO.	DATE	NOTES
1	11.23.21	KENDALL COUNTY REVIEW EMAIL 11.23.21
2	12.13.21	WBK SITE PLAN REVIEW 12.06.21
3	12.29.21	WBK REVIEW EMAIL 12.27.21





PARKING EXHIBIT

EXISTING PARKING STALLS - 36
 EXISTING HANDICAP STALLS - 2
 TOTAL PACKING STALLS - 38



- Place the end post of the second fence inside the end post of the first fence.
- Rotate both posts at least 180 degrees in a clockwise direction to create a tight seal with the fabric material.
- Cut the fabric near the bottom of the stakes to accommodate the 6" gap.
- Drive both posts a minimum of 18 inches into the ground and bury the top.
- Compact backfill (particularly at splices) completely to prevent stormwater piping.


CONCRETE WASHOUT NOTE:
 CONCRETE WASHOUT SHOULD BE CONTAINED AT ALL TIMES. WASHOUT MATERIAL SHOULD NOT BE ALLOWED TO ENTER WATER BODIES, STORM SEWERS OR LEACH INTO THE SOIL UNDER ANY CIRCUMSTANCES. ANY WASTE SHOULD BE DISPOSED OF PROPERLY AND THE LOCATION OF THE WASHOUT SHOULD BE DESIGNATED WITH PROPER SIGNAGE. FAILURE TO COMPLY COULD RESULT IN AN INCIDENCE OF NONCOMPLIANCE (ICN).





- NOTES:**
- Temporary sediment fence shall be installed prior to any grading work in the area to be protected. They shall be maintained throughout the construction period and removed in conjunction with the final grading and site stabilization.
 - Filter fabric shall meet the requirements of material specification 562 Geotextile Table 1 or 2, Class with equivalent opening size of at least 30 for nonweave and 40 for weave.
 - Fence posts shall be either standard steel post or wood post with a minimum cross-sectional area of 3.0 sq. in.



NO.	DATE	NOTES



TOTAL NEW & EXISTING STALLS - 61
 TOTAL NEW & EXISTING HANDICAP STALLS - 3
 TOTAL PARKING STALLS - 64



TEBRUGGE ENGINEERING
 410 E. CHURCH STREET - SUITE A • SANDWICH, IL 60548
 PHONE: (815) 786-0195 TEBRUGGEENGINEERING.COM

NO.	DATE	NOTES

PREPARED FOR:
TMF MANAGEMENT, LLC
 12127 GALENA RD-UNIT B, PLANO, IL 60545

TMF MANAGEMENT, LLC PARKING ADDITION
CIVIL SITE PLAN

PROJECT NO.	21 504 01	SHEET NO.	3
SCALE:	1" = 20'		
DATE:	APRIL 4, 2022		

OF 4 SHEETS

**STORMWATER MANAGEMENT
FEE-IN-LIEU DESIGN COMPUTATIONS
FOR TMF PLASTICS SOUTH PARKING LOT ADDITION
LOCATED AT 12127B GALENA ROAD - PLANO, IL IN KENDALL COUNTY**
BY
**TEBRUGGE ENGINEERING
410 E. CHURCH ST. SUITE A
SANDWICH, IL
REVISED 12.13.21**

TMF PLASTICS IS PLANNING TO CONSTRUCT A SMALL PARKING LOT ADDITION ON THE SOUTH PARKING LOT COVERING 2,832 SF. DUE TO SITE CONSTRAINTS ALONG THE SOUTH PROPERTY LINE, WE ARE PROVIDING FEE-IN-LIEU CALCULATIONS FOR THE 2,832 SF OF NEW IMPERVIOUS AREA IN THE SOUTH PARKING LOT.

NEW ASPHALT PAVEMENT = 2,832 SF = 0.065 AC
CN = 96

HYDROGRAPH REPORT No.10 SHOWS A REQUIRED STORAGE VOLUME = 1,285 CF = 0.029 AC-FT.

A 2 FOOT DEEP POND WAS ANALYZED COVERING AN AREA OF APPROXIMATELY 1560 SF

EXCAVATION COST : $2000 \text{ CF} / 27 = 74 \text{ CY} \times \$20/\text{CY} = \$1,480.$

TOPSOIL COST $540 \text{ CF} / 27 = 20 \text{ CY} \times \$20/\text{CY} = \$ 400$

OUTFALL PIPE & INLET = \$ 700

SEEDING \$120

TOTAL COST FOR FEE IN LIEU = \$2,700.00



EXPIRES 11.30.23

Hydrograph Report


Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2021

Wednesday, 03 / 30 / 2022

Hyd. No. 10

south parking lot 2832SF TMF - *SOUTH PARKING LOT - FEE IN LIEU*

Hydrograph type	= SCS Runoff	Peak discharge	= 0.842 cfs
Storm frequency	= 100 yrs	Time to peak	= 11.92 hrs
Time interval	= 1 min	Hyd. volume	= 1,789 cuft
Drainage area	= 0.065 ac	Curve number	= 96
Basin Slope	= 1.0 %	Hydraulic length	= 80 ft
Tc method	= LAG	Time of conc. (Tc)	= 2.24 min
Total precip.	= 8.57 in	Distribution	= Type II
Storm duration	= 24 hrs	Shape factor	= 484



Hydrograph Report

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2021


Wednesday, 03 / 30 / 2022

Hyd. No. 11

Fee in lieu Analysis - *TMF PLASTICS - SOUTH PARKING LOT*

Hydrograph type	= Reservoir	Peak discharge	= 0.012 cfs
Storm frequency	= 100 yrs	Time to peak	= 15.95 hrs
Time interval	= 1 min	Hyd. volume	= 1,485 cuft
Inflow hyd. No.	= 10 - south parking lot 2832SF	TMF Elevation	= 675.48 ft
Reservoir name	= fee in lieu pond	Max. Storage	= 1,268 cuft

Storage Indication method used.



Hydrograph Report

Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2021

Wednesday, 03 / 30 / 2022

Hyd. No. 11


Fee in lieu Analysis

Hydrograph type	= Reservoir	Peak discharge	= 0.012 cfs
Storm frequency	= 100 yrs	Time to peak	= 15.95 hrs
Time interval	= 1 min	Hyd. volume	= 1,485 cuft
Inflow hyd. No.	= 10 - south parking lot 2832SF	Max. Elevation	= 675.48 ft
Reservoir name	= fee in lieu pond	Max. Storage	= 1,268 cuft

Storage Indication method used.

Fee in lieu Analysis

Hyd. No. 11 -- 100 Year





May 6, 2022

Mr. Matt Asselmeier
Kendall County Planning, Building, & Zoning
111 West Fox Street
Yorkville, IL 60560-1498

Subject: 12127B Galena Road TMF Management South Parking Lot Addition
(WBK Project 19-102.AK)

Dear Mr. Asselmeier:

We have received the following information for the subject project:

- Stormwater Management Fee-In-Lieu Computations for TMF Plastics South Parking Lot Addition prepared by Tebrugge Engineering dated December 13, 2021 and received April 29, 2022.
- Engineering Plans for TMF Management Building Addition prepared by Tebrugge Engineering dated April 26, 2022 and received April 29, 2022.

We find the fee-in-lieu calculations and engineering plans to be acceptable. Contact our office prior to construction of the parking area to verify erosion control measures.

The applicant's design professionals are responsible for performing and checking all design computations, dimensions, details, and specifications in accordance with all applicable codes and regulations, and obtaining all permits necessary to complete this work. In no way does this review relieve applicant's design professionals of their duties to comply with the law and any applicable codes and regulations, nor does it relieve the Contractors in any way from their sole responsibility for the quality and workmanship of the work and for strict compliance with the permitted plans and specifications. If you have any questions or comments, please contact us at (630) 443-7755.

Sincerely,


Gre

WBK Engineering, LLC





DEPARTMENT OF PLANNING, BUILDING & ZONING

111 West Fox Street • Room 204

Yorkville, IL • 60560

(630) 553-4141

Fax (630) 553-4179

December 8, 2021

Tim Raymond
TMF Plastic Solutions, LLC
12127 Galena Road Unit B
Plano, IL 60545

RE: *Site Plan Approval for Building Addition*
12127 Galena Road, Unit B, Plano, Little Rock Township (PIN # 01-01-200-002)


Dear Mr. Raymond:

At their meeting on December 7, 2021, the Kendall County ZPAC approved the site plan at the above referenced property for the construction of an approximately twenty thousand six hundred thirty (20,630) square foot addition to the north and east of the existing approximately forty-five thousand six hundred ninety-two (45,692) square foot building located on Parcel One of the subject property. The proposal also calls for a stormwater pond north of the proposed addition. The addition will consist of two (2) new loading docks on the on the southeast side of the addition. This approval is conditional on the following:

1. The site plan approved in 2008 shall be amended to incorporate the subject site plan.
2. The site shall be developed substantially in conformance with the attached site plan, civil plan, photometric plan, and elevations. The metal siding shall be gray to match the existing building.
3. The November 23, 2021, letter from Tebrugge Engineering will be included as part of the site plan.
4. The site shall be developed in accordance with all applicable federal, state, and local laws related to site development and the type of use proposed for the site, including, but not limited to, securing the applicable building and stormwater permits.

Should you have any questions or concerns about this matter, please feel free to me at (630) 553-4139 or masselmeier@co.kendall.il.us.

Kind Regards,


Matthew H. Asselmeier, AICP, CFM
Senior Planner

PIN: 01-01-200-013
 OWNER: KONICEK FAMILY LTD.
 PARTNERSHIP PER DOC. 0000277
 ZONING: A1 - AGRICULTURAL

SITE DATA:

TOTAL ACRES - 6.0 AC
 EXISTING PARKING - 39 STALLS
 2 HANDICAP
 NEW PARKING - 0 STALLS

BUILDING COVERAGE:

EXISTING BLDGS - 83,227 S.F.
 PROPOSED BLDGS - 20,630 S.F.
 TOTAL BLDGS - 103,857 S.F.
 TOTAL LOT - 261,359 S.F.
 SITE COVERAGE - 40%

PIN: 01-01-200-024
 OWNER: WADE R JOYNER &
 TRACEY FISHER-JOYNER PER
 DOC. 9605497
 ZONING: A1-BP -
 AGRICULTURAL

PROPOSED BUILDING
 ADDITION
 FF = 671.81

EXISTING COMMERCIAL
 BUILDING
 45,692 SF
 FF = 671.81

PIN: 01-01-200-002
 OWNER: TMF MANAGEMENT
 ZONING: M1 - LIMITED
 MANUFACTURING

1-Story Corrugated
 Metal Building
 35,720 SF
 #12127 B Galena Rd.




1-Story Frame
 Building

1-Story Corrugated
 Metal Building
 19,256 SF

PIN: 01-01-200-003
 OWNER: OLD SECOND
 NATIONAL BANK OF
 AURORA AS TRUSTEE
 UNDER TRUST #5801 PER
 DOC. 9500700
 ZONING: M1 - LIMITED
 MANUFACTURING

PIN: 01-01-200-015
 OWNER: BRYAN W & DIANE M
 APPEL PER DOC. 9710644
 ZONING: A1 - AGRICULTURAL

PIN: 01-01-200-022
 OWNER: ROBERT E DAVIDSON JR.
 PER DOC. 9710645
 ZONING: A1 - AGRICULTURAL



NO.	DATE	NOTES
1	11.23.21	KENDALL COUNTY REVIEW EMAIL 11.23.21

ENGINEERING PLANS FOR TMF PLASTIC BUILDING ADDITION


SECTION 1, TOWNSHIP 37 NORTH, RANGE 6 EAST

12127B GALENA RD
PLANO, IL 60545
KENDALL COUNTY
NOVEMBER, 2021

LEGEND	
---	PROPERTY BOUNDARY
---600---	EXISTING CONTOUR LINE
---	EXISTING STORM SEWER
---	EXISTING SANITARY SEWER LINE
---	EXISTING WATERMAIN
---	EXISTING UNDERGROUND ELECTRIC
---	EXISTING OVERHEAD ELECTRIC
---	EXISTING GAS SERVICE
---	EXISTING TELEPHONE
---	PROPOSED CONTOUR LINE
---	PROPOSED WATERMAIN
---	PROPOSED STORM SEWER
---	PROPOSED SANITARY SEWER LINE
---	PROPOSED GREASE SERVICE LINE
---	PROPOSED VENT LINE
---	EXISTING FENCELINE
---	PROPOSED SILT FENCE
x 686.00	EXISTING SPOT SHOT
x 686.00	PROPOSED SPOT GRADE
EXIST	PROP
WATER: ○	B-BOX
○	HYDRANT
○	VALVE
○	VALVE VAULT
STORM: □	INLET-CURB
○	INLET OR MANHOLE
▽	FLARED END SECTION
SANITARY: ○	CLEANOUT
○	MANHOLE
⊗	R.O.W. MONUMENT
⊗	PROPERTY PIN
▲	P.K. NAIL
■	CHISELED MARK
■	BENCHMARK
⊗	HUB & TACK
⊗	SOIL BORING
→	OVERLAND RELIEF
→	FLOW DIRECTION
○	UTILITY POLE
○	GUY WIRE LOC.
□	UTIL CABINET
□	UTIL PEDESTAL
○	LIGHT POLE
○	TRAFFIC SIGNAL
○	ELECTRIC VAULT
○	GAS VALVE

INDEX TO SHEETS

1. COVER SHEET
2. EXISTING CONDITIONS & DEMOLITION PLAN
3. OVERALL SITE PLAN
4. CIVIL SITE PLANS
5. GENERAL NOTES & DETAILS



PROJECT LOCATION

BENCHMARKS:

1. NATIONAL GEODETIC SURVEY MONUMENT PID - MF0523
LOCATED 320 FEET EAST OF THE PLANO TRAIN STATION, 21 FEET NORTH OF THE CENTERLINE OF THE NORTH TRACK, AT AN ABANDONED SIGNAL BRIDGE FOUNDATION STANDARD DISK IN CONCRETE STAMPED "Y 49 1934"
NAVD 88 DATUM
ELEVATION = 649.12
2. ON-SITE BENCHMARK NORTH EAST CORNER OF ELECTRIC TRANSFORMER PAD (LOCATION ON PLAN)
NAVD 88 DATUM
ELEVATION = 671.88

PLANS PREPARED FOR:

TMF PLASTIC SOLUTIONS, LLC
12127 GALENA ROAD - UNIT B
PLANO, IL 60545
PHONE: (630) 552-7575

CIVIL ENGINEER:

TEBRUGGE ENGINEERING
410 E CHURCH ST - SUITE A
SANDWICH, ILLINOIS 60548
(815) 786-0195
INFO@TEBRUGGEENGINEERING.COM
WWW.TEBRUGGEENGINEERING.COM



Know what's below.
Call before you dig.

Contractor and or sub-contractors shall verify locations of all underground utilities prior to digging. Contact J.U.L.I.E. (Joint Utility Locating for Excavators) at 1-800-892-0123 or dial 811.


UTILITY STATEMENT

THE UTILITIES SHOWN HAVE BEEN LOCATED FROM VISIBLE FIELD EVIDENCE AND EXISTING DRAWINGS, MAPS AND RECORDS SUPPLIED TO SURVEYOR. THE SURVEYOR MAKES NO GUARANTEES THAT THE UTILITIES SHOWN COMPRISE ALL SUCH UTILITIES IN THE AREA, EITHER IN SERVICE OR ABANDONED. THE SURVEYOR FURTHER DOES NOT WARRANT THAT THE UTILITIES SHOWN ARE IN THE EXACT LOCATION INDICATED, ALTHOUGH THEY ARE LOCATED AS ACCURATELY AS POSSIBLE FROM AVAILABLE INFORMATION. THE SURVEYOR HAS PHYSICALLY LOCATED VISIBLE STRUCTURES; HOWEVER, HE HAS NOT PHYSICALLY LOCATED THE UNDERGROUND LINES.

PROFESSIONAL ENGINEER'S CERTIFICATION
STATE OF ILLINOIS, COUNTY OF KENDALL

I JOHN J. TEBRUGGE, A LICENSED PROFESSIONAL ENGINEER OF ILLINOIS, HEREBY CERTIFY THAT THESE PLANS HAVE BEEN PREPARED UNDER MY PERSONAL DIRECTION BASED ON AVAILABLE DOCUMENTS AND FIELD MEASUREMENTS FOR THE EXCLUSIVE USE OF THE CLIENT NOTED HEREON.


GIVEN UNDER MY HAND & SEAL THIS 23RD DAY OF NOVEMBER, 2021



ILLINOIS REGISTERED PROFESSIONAL ENGINEER
NO. 0123456789 EXPIRES NOV. 30, 2021

COPYRIGHT © 2021 BY TEBRUGGE ENGINEERING
ALL RIGHTS RESERVED. NO PART OF THESE CIVIL ENGINEERING PLANS MAY BE REPRODUCED, DISTRIBUTED, OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, INCLUDING PHOTOCOPYING, RECORDING, OR OTHER ELECTRONIC OR MECHANICAL METHODS, WITHOUT THE PRIOR WRITTEN PERMISSION OF TEBRUGGE ENGINEERING.


NO.	DATE	NOTES
1	11.23.21	KENDALL COUNTY REVIEW EMAIL 11.23.21



PIN: 01-01-200-015



PIN: 01-01-200-002
 OWNER: TMF MANAGEMENT
 ZONING: M1 - LIMITED
 MANUFACTURING

PARCEL ONE
 261,259 S.F.
 6.000 ACRES,
 MORE OR LESS




- Place the end post of the second fence inside the end post of the first fence.
- Rotate both posts at least 180 degrees in a clockwise direction to create a tight seal with the fabric material.
- Cut the fabric near the bottom of the stakes to accommodate the 6" gap.
- Drive both posts a minimum of 18 inches into the ground and bury the top.
- Compact backfill (particularly at splices) completely to prevent stormwater piping.

CONCRETE WASHOUT NOTE:
 CONCRETE WASHOUT SHOULD BE CONTAINED AT ALL TIMES. WASHOUT MATERIAL SHOULD NOT BE ALLOWED TO ENTER WATER BODIES, STORM SEWERS OR LEACH INTO THE SOIL UNDER ANY CIRCUMSTANCES. ANY WASTE SHOULD BE DISPOSED OF PROPERLY AND THE LOCATION OF THE WASHOUT SHOULD BE DESIGNATED WITH PROPER SIGNAGE. FAILURE TO COMPLY COULD RESULT IN AN INCIDENCE OF NONCOMPLIANCE (ICN).



NOTES:
 1. Temporary sediment fence shall be installed prior to any grading work in the area to be protected. They shall be maintained throughout the construction period and removed in conjunction with the final grading and site stabilization.
 2. Filter fabric shall meet the requirements of material specification 562 Genesee Table 1 or 2, Class with equivalent opening size of at least 30 for manure and 40 for weeds.
 3. Fence posts shall be either standard steel post or wood post with a minimum cross-sectional area of 3.0 sq. in.



TEBRUGGE ENGINEERING
 410 E. CHURCH STREET - SUITE A • SANDWICH, IL 60548
 PHONE: (815) 786-0195 TEBRUGGEENGINEERING.COM


NO.	DATE	NOTES
1	11.23.21	KENDALL COUNTY REVIEW EMAIL 11.23.21

PREPARED FOR:
TMF PLASTIC SOLUTIONS, LLC
 12127 GALENA RD-UNIT B, PLANO, IL 60545

TMF PLASTIC BUILDING ADDITION
EXISTING CONDITIONS & DEMOLITION PLAN

PROJECT NO. 21 504 01
 SCALE: 1" = 20'
 DATE: NOV 15, 2021

SHEET NO. **2**
 OF 5 SHEETS





TEBRUGGE ENGINEERING		NO.	DATE	NOTES
410 E. CHURCH STREET - SUITE A • SANDWICH, IL 60548 PHONE: (815) 786-0195		1	11.23.21	KENDALL COUNTY REVIEW EMAIL 11.23.21
TEBRUGGEENGINEERING.COM				

PREPARED FOR:
TMF PLASTIC SOLUTIONS, LLC
 12127 GALENA RD-UNIT B, PLANO, IL 60545

TMF PLASTIC BUILDING ADDITION
OVERALL SITE PLAN


PROJECT NO.	21 504 01	SHEET NO.	3
SCALE:	1" = 20'		
DATE:	NOV 15, 2021		



BUILDING COVERAGE:

EXISTING BLDGS - 83,227 S.F.
 PROPOSED BLDGS - 20,630 S.F.
 TOTAL BLDGS - 103,857 S.F.

TOTAL LOT - 261,359 S.F.
 SITE COVERAGE - 40%



GENERAL CONDITIONS

1. ALL EARTHWORK, ROADWAY WORK, DRAINAGE WORK OR STORM SEWER WORK SHALL BE PERFORMED UTILIZING MATERIALS AND METHODS IN STRICT ACCORDANCE WITH THE ILLINOIS DEPARTMENT OF TRANSPORTATION "STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION" LATEST EDITION, AS WELL AS THE STANDARD DETAIL SHEETS ATTACHED TO THESE PLANS. ALL MUNICIPAL, COUNTY, STATE AND FEDERAL REQUIREMENTS AND STANDARDS SHALL BE STRICTLY ADHERED TO IN WORK PERFORMED UNDER THIS CONTRACT.
2. ALL SANITARY SEWER AND WATER MAIN WORK SHALL BE PERFORMED USING METHODS AND MATERIALS IN STRICT ACCORDANCE WITH THE LATEST EDITION OF "STANDARD SPECIFICATIONS FOR WATER AND SEWER MAIN CONSTRUCTION IN ILLINOIS" LATEST EDITION, AS WELL AS THE STANDARD DETAIL SHEETS ATTACHED TO THESE PLANS. ALL MUNICIPAL, COUNTY, STATE AND FEDERAL REQUIREMENTS AND STANDARDS SHALL BE STRICTLY ADHERED TO IN WORK PERFORMED UNDER THIS CONTRACT.
3. ANY SPECIFICATIONS WHICH ARE SUPPLIED ALONG WITH THE PLANS SHALL TAKE PRECEDENCE IN THE CASE OF A CONFLICT WITH THE STANDARD SPECIFICATIONS NOTED IN ITEMS NO. 1 AND 2 ABOVE. THE ABOVE STANDARD SPECIFICATIONS & THE CONSTRUCTION PLANS ARE TO BE CONSIDERED AS PART OF THE CONTRACT DOCUMENTS. INCIDENTAL ITEMS OR ACCESSORIES NECESSARY TO COMPLETE THIS WORK MAY NOT BE SPECIFICALLY NOTED BUT ARE TO BE CONSIDERED A PART OF THE CONTRACT.
4. PRIOR TO COMMENCEMENT OF CONSTRUCTION, THE CONTRACTOR SHALL VERIFY ALL DIMENSIONS AND CONDITIONS AFFECTING THEIR WORK WITH THE ACTUAL CONDITIONS AT THE JOB SITE. IF THERE ARE ANY DISCREPANCIES FROM WHAT IS SHOWN ON THE CONSTRUCTION PLANS, HE MUST IMMEDIATELY REPORT SAME TO THE ENGINEER BEFORE DOING ANY WORK, OTHERWISE THE CONTRACTOR WILL BE CONSIDERED TO HAVE PROCEEDED AT HIS OWN RISK AND EXPENSE. IN THE EVENT OF ANY DOUBT OR QUESTION ARISING WITH RESPECT TO THE TRUE MEANING OF THE CONSTRUCTION PLANS OR SPECIFICATIONS, THE DECISION OF THE ENGINEER SHALL BE FINAL AND CONCLUSIVE.
5. ALL WORK PERFORMED UNDER THIS CONTRACT SHALL BE GUARANTEED AGAINST ALL DEFECTS IN MATERIALS AND WORKMANSHIP OF WHATEVER NATURE BY THE CONTRACTOR AND HIS SURETY FOR A PERIOD OF 12 MONTHS FROM THE DATE OF FINAL ACCEPTANCE OF THE WORK BY THE GOVERNING MUNICIPALITY, OTHER APPLICABLE GOVERNMENTAL AGENCIES, AND THE OWNER.
6. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL REQUIRED PERMITS FOR CONSTRUCTION ALONG OR ACROSS EXISTING STREETS OR HIGHWAYS. HE SHALL MAKE ARRANGEMENTS FOR BRACING OR SHORING AND OTHER REQUIRED PROTECTION OF ALL ROADWAYS BEFORE CONSTRUCTION BEGINS, ALONG WITH ADEQUATE TRAFFIC CONTROL MEASURES. HE SHALL BE RESPONSIBLE FOR ANY DAMAGE TO THE STREETS OR ROADWAYS AND ASSOCIATED STRUCTURES AND SHALL MAKE REPAIRS AS NECESSARY TO THE SATISFACTION OF THE ENGINEER, AT NO ADDITIONAL COST TO THE OWNER.
7. THE UTILITY LOCATIONS, AND THE DEPTHS SHOWN ON THESE PLANS ARE APPROXIMATE ONLY, AND SHALL BE VERIFIED BY THE CONTRACTOR WITH ALL AFFECTED UTILITY COMPANIES PRIOR TO INITIATING CONSTRUCTION OPERATIONS. THE ENGINEER AND OWNER ASSUME NO RESPONSIBILITY FOR THE ADEQUACY, SUFFICIENCY OR EXACTNESS OF THESE UTILITY REPRESENTATIONS.
8. PRIOR TO STARTING CONSTRUCTION THE CONTRACTOR SHALL CONTACT THE OFFICE OF J.U.L.I.E. AT 1-800-892-0123 FOR EXACT FIELD LOCATION OF ALL UNDERGROUND UTILITIES IN THE PROXIMITY OF, AND ON, THE PROJECT SITE. IF THERE ARE ANY UTILITIES WHICH ARE NOT MEMBERS OF THE J.U.L.I.E. SYSTEM, THE CONTRACTOR SHALL BE SOLELY RESPONSIBLE FOR DETERMINING THIS AND MAKE ARRANGEMENTS TO HAVE THESE UTILITIES FIELD LOCATED.
9. EASEMENTS FOR THE EXISTING UTILITIES, BOTH PUBLIC AND PRIVATE, AND UTILITIES WITHIN PUBLIC RIGHTS-OF-WAY ARE SHOWN ON THE PLANS ACCORDING TO AVAILABLE RECORDS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR DETERMINING THE EXACT LOCATION IN THE FIELD OF THESE UTILITY LINES AND THEIR PROTECTION FROM DAMAGE DUE TO CONSTRUCTION OPERATIONS. IF EXISTING UTILITY LINES OF ANY NATURE ARE ENCOUNTERED WHICH CONFLICT IN LOCATION WITH NEW CONSTRUCTION, THE CONTRACTOR SHALL BE SOLELY RESPONSIBLE FOR RELOCATING THESE FACILITIES AT HIS EXPENSE TO ACCOMMODATE THE NEW CONSTRUCTION.
10. ALL FIELD TILE ENCOUNTERED DURING CONSTRUCTION OPERATIONS SHALL BE CONNECTED TO THE PROPOSED STORM SEWER OR EXTENDED TO OUTLET INTO A PROPOSED DRAINAGE WAY. IF THIS CANNOT BE ACCOMPLISHED, THEN IT SHALL BE REPAIRED WITH NEW PIPE OF SIMILAR SIZE AND MATERIAL TO THE ORIGINAL LINE AND PUT IN ACCEPTABLE OPERATIONAL CONDITION. A RECORD OF THE LOCATION OF ALL FIELD TILE FOR ON-SITE DRAIN PIPE ENCOUNTERED SHALL BE KEPT BY THE CONTRACTOR AND TURNED OVER TO THE ENGINEER UPON COMPLETION OF THE PROJECT. THE COST OF THIS WORK SHALL BE CONSIDERED AS INCIDENTAL TO THE CONTRACT AND NO ADDITIONAL COMPENSATION WILL BE ALLOWED.
11. IT SHALL BE THE RESPONSIBILITY OF EACH RESPECTIVE CONTRACTOR TO REMOVE FROM THIS SITE ANY AND ALL MATERIALS AND DEBRIS WHICH RESULT FROM HIS CONSTRUCTION OPERATIONS AT NO ADDITIONAL EXPENSE TO THE OWNER.
12. THE ENGINEER AND OWNER ARE NOT RESPONSIBLE FOR THE CONSTRUCTION MEANS, METHODS, TECHNIQUES, SEQUENCES OR PROCEDURES, TIME OF PERFORMANCE, PROGRAMS OF FOR ANY SAFETY PRECAUTIONS USED BY THE CONTRACTOR. THE CONTRACTOR IS SOLELY RESPONSIBLE FOR EXECUTION OF HIS WORK IN ACCORDANCE WITH THE CONTRACT DOCUMENTS AND SPECIFICATIONS.
13. THE CONTRACTOR SHALL COMPLY WITH ALL STATE AND FEDERAL SAFETY REGULATIONS AS OUTLINED IN THE LATEST REVISIONS OF THE FEDERAL CONSTRUCTION SAFETY STANDARDS (SERIES 1928) AND WITH APPLICABLE PROVISIONS AND REGULATIONS OF THE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA) STANDARDS OF THE WILLIAMS STELGER OCCUPATIONAL HEALTH STATE SAFETY ACT OF 1970 (REVISED). THE CONTRACTOR, ENGINEERS, AND OWNER SHALL EACH BE RESPONSIBLE FOR HIS OWN RESPECTIVE AGENTS AND EMPLOYEES.
14. THE CONTRACTOR SHALL INDEMNIFY THE OWNER, THE ENGINEER, AND ALL GOVERNING AUTHORITIES, THEIR AGENTS SUCCESSORS AND ASSIGNS FROM ANY AND ALL LIABILITY WITH RESPECT TO THE CONSTRUCTION, INSTALLATION AND TESTING OF THE WORK REQUIRED ON THIS PROJECT. IT SHALL BE THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO PERFORM THE WORK OF THIS CONTRACT IN A MANNER WHICH STRICTLY COMPLIES WITH ANY AND ALL PERTINENT LOCAL, STATE OR NATIONAL CONSTRUCTION AND SAFETY CODES; THE ENGINEER, OWNER, AND GOVERNING AUTHORITIES ARE NOT RESPONSIBLE FOR ENSURING COMPLIANCE BY THE CONTRACTOR WITH SAID CODES AND ASSUME NO LIABILITY FOR ACCIDENTS, INJURIES, OR DEATHS, OR CLAIMS RELATING THERETO WHICH MAY RESULT FROM LACK OF ADHERENCE TO SAID CODES.

NO.	DATE	NOTES
1	11.23.21	KENDALL COUNTY REVIEW EMAIL 11.23.21


EARTHWORK

1. ALL EARTHWORK OPERATIONS SHALL BE IN ACCORDANCE WITH SECTION 200 OF THE I.D.O.T. SPECIFICATIONS.
2. THE CONTRACTOR SHALL PROTECT ALL PROPERTY PINS AND SURVEY MONUMENTS AND SHALL RESTORE ANY WHICH ARE DISTURBED BY HIS OPERATIONS AT NO ADDITIONAL COST TO THE CONTRACT.
3. IT IS THE CONTRACTOR'S RESPONSIBILITY TO DETERMINE ALL MATERIAL QUANTITIES AND APPRISE HIMSELF OF ALL SITE CONDITIONS. THE CONTRACT PRICE SUBMITTED BY THE CONTRACTOR SHALL BE CONSIDERED AS LUMP SUM FOR THE COMPLETE PROJECT. NO CLAIMS FOR EXTRA WORK WILL BE RECOGNIZED UNLESS ORDERED IN WRITING BY THE OWNER.
4. PRIOR TO ONSET OF MASS GRADING OPERATIONS THE EARTHWORK CONTRACTOR SHALL FAMILIARIZE HIMSELF WITH THE SOIL EROSION CONTROL SPECIFICATIONS, THE INITIAL ESTABLISHMENT OF EROSION CONTROL PROCEDURES AND THE PLACEMENT OF SILT FENCING, ETC. TO PROTECT ADJACENT PROPERTY SHALL OCCUR BEFORE MASS GRADING BEGINS, AND IN ACCORDANCE WITH THE SOIL EROSION CONTROL CONSTRUCTION SCHEDULE.
5. THE GRADING OPERATIONS ARE TO BE CLOSELY SUPERVISED AND INSPECTED, PARTICULARLY DURING THE REMOVAL OF UNSUITABLE MATERIAL AND THE CONSTRUCTION OF EMBANKMENTS OR BUILDING PADS, BY THE SOILS ENGINEER OR HIS REPRESENTATIVE. ALL TESTING, INSPECTION AND SUPERVISION OF SOIL QUALITY, UNSUITABLE REMOVAL AND ITS REPLACEMENT AND OTHER SOILS RELATED OPERATIONS SHALL BE ENTIRELY THE RESPONSIBILITY OF THE SOILS ENGINEER.
6. THE GRADING AND CONSTRUCTION OF THE SITE IMPROVEMENTS SHALL NOT CAUSE PONDING OF STORM WATER. ALL AREAS ADJACENT TO THESE IMPROVEMENTS SHALL BE GRADED TO ALLOW POSITIVE DRAINAGE.
7. THE PROPOSED GRADING ELEVATIONS SHOWN ON THE PLANS ARE FINISH GRADE. A MINIMUM OF SIX INCHES (6") OF TOPSOIL IS TO BE PLACED BEFORE FINISH GRADE ELEVATIONS ARE ACHIEVED.
8. THE SELECTED STRUCTURAL FILL MATERIAL SHALL BE PLACED IN LEVEL UNIFORM LAYERS SO THAT THE COMPACTED THICKNESS IS APPROXIMATELY SIX INCHES (6"). IF COMPACTION EQUIPMENT DEMONSTRATES THE ABILITY TO COMPACT A GREATER THICKNESS, THEN A GREATER THICKNESS MAY BE SPECIFIED. EACH LAYER SHALL BE THOROUGHLY MIXED DURING SPREADING TO INSURE UNIFORMITY.
9. EMBANKMENT MATERIAL WITHIN ROADWAY, PARKING LOT, AND OTHER STRUCTURAL CLAY FILL AREAS SHALL BE COMPACTED TO A MINIMUM OF NINETY-FIVE PERCENT (95%) OF MAXIMUM DENSITY IN ACCORDANCE WITH ASTM SPECIFICATION D-1557 (MODIFIED PROCTOR METHOD), OR TO SUCH OTHER DENSITY AS MAY BE DETERMINED APPROPRIATE BY THE SOILS ENGINEER. EMBANKMENT MATERIAL FOR BUILDING PADS SHALL BE COMPACTED TO A MINIMUM OF NINETY-FIVE (95%) OF MAXIMUM DENSITY IN ACCORDANCE WITH ASTM DESIGNATION D-1557 (MODIFIED PROCTOR METHOD) OR TO SUCH OTHER DENSITY AS MAY BE DETERMINED APPROPRIATE BY THE SOILS ENGINEER.
10. EMBANKMENT MATERIAL (RANDOM FILL) WITHIN NON-STRUCTURAL FILL AREAS SHALL BE COMPACTED TO A MINIMUM OF NINETY PERCENT (90%) OF MAXIMUM DENSITY IN ACCORDANCE WITH ASTM SPECIFICATION D-157 (MODIFIED PROCTOR METHOD).
11. THE SUB GRADE FOR PROPOSED STREET AND PAVEMENT AREAS SHALL BE PROOF-ROLLED BY THE CONTRACTOR AND ANY UNSTABLE AREAS ENCOUNTERED SHALL BE REMOVED AND REPLACED AS DIRECTED BY THE SOILS ENGINEER.
12. SOIL BORING REPORTS, IF AVAILABLE, ARE SOLELY FOR THE INFORMATION AND GUIDANCE OF THE CONTRACTORS. THE OWNER AND ENGINEER MAKE NO REPRESENTATION OR WARRANTY REGARDING THE INFORMATION CONTAINED IN THE BORING LOGS. THE CONTRACTOR SHALL MAKE HIS OWN INVESTIGATIONS AND SHALL PLAN HIS WORK ACCORDINGLY. ARRANGEMENTS TO ENTER THE PROPERTY DURING THE BIDDING PHASE MAY BE MADE UPON REQUEST OF THE OWNER. THERE WILL BE NO ADDITIONAL PAYMENT FOR EXPENSES INCURRED BY THE CONTRACTOR RESULTING FROM ADVERSE SOIL OR GROUND WATER CONDITIONS.
13. IT SHALL BE THE RESPONSIBILITY OF THE EXCAVATION CONTRACTOR TO REMOVE FROM THE SITE ANY AND ALL MATERIALS AND DEBRIS WHICH RESULT FROM HIS CONSTRUCTION OPERATIONS AT NO ADDITIONAL EXPENSE TO THE OWNER.


PAVING & WALKS

1. WORK UNDER THIS SECTION SHALL INCLUDE FINAL SUBGRADE SHAPING AND PREPARATION: FORMING, JOINING, PLACEMENT OF ROADWAY AND PAVEMENT BASE COURSE MATERIALS AND SUBSEQUENT BINDER AND/OR SURFACE COURSES; PLACEMENT, FINISHING AND CURING OF CONCRETE; FINAL CLEAN-UP; AND ALL RELATED WORK.
2. ALL PAVING AND SIDEWALK WORK SHALL BE DONE IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS (I.D.O.T.) AND PER LOCAL REGULATIONS.
3. SUBGRADE FOR PROPOSED PAVEMENT SHALL BE FINISHED BY THE EXCAVATION CONTRACTOR TO WITHIN 0.1 FOOT, PLUS OR MINUS, OF THE PLAN ELEVATION. THE PAVING CONTRACTOR SHALL SATISFY HIMSELF THAT THE SUBGRADE HAS BEEN PROPERLY PREPARED AND THAT THE FINISH TOP SUBGRADE ELEVATION HAS BEEN GRADED WITHIN TOLERANCES ALLOWED IN THESE SPECIFICATIONS. UNLESS THE PAVING CONTRACTOR ADVISES THE OWNER AND ENGINEER IN WRITING PRIOR TO FINE GRADING FOR BASE COURSE CONSTRUCTION, IT IS UNDERSTOOD THAT HE HAS APPROVED AND ACCEPTS THE RESPONSIBILITY FOR THE SUBGRADE. PRIOR TO PLACEMENT OF PAVEMENT BASE MATERIALS, THE PAVING CONTRACTOR SHALL FINE GRADE THE SUBGRADE SO AS TO INSURE THE PROPER THICKNESS OF PAVEMENT COURSES. NO CLAIMS FOR EXCESS BASE MATERIALS DUE TO IMPROPER SUBGRADE PREPARATION WILL BE HONORED.
4. THE PROPOSED PAVEMENT SHALL CONSIST OF THE SUB-BASE COURSE, BITUMINOUS AGGREGATE BASE COURSE, BITUMINOUS BINDER COURSE, AND BITUMINOUS SURFACE COURSE. OF THE THICKNESS AND MATERIALS AS SPECIFIED ON THE CONSTRUCTION PLANS. PRIME COAT SHALL BE APPLIED TO THE SUB-BASE COURSE AT A RATE OF 0.5 GALLONS PER SQUARE YARD. UNLESS SHOWN AS A BID ITEM, PRIME COAT SHALL BE CONSIDERED AS INCIDENTAL TO THE COST OF THE CONTRACT. ALL PAVEMENT SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE "I.D.O.T. STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION", CURRENT EDITION.
5. AFTER THE INSTALLATION OF THE BASE COURSE, ALL TRAFFIC SHALL BE KEPT OFF THE BASE UNTIL THE BINDER COURSE IS LAID. AFTER INSTALLATION OF THE BINDER COURSE AND UPON INSPECTION AND APPROVAL BY GOVERNING AUTHORITY, THE PAVEMENT SHALL BE CLEANED, PRIMED AND THE SURFACE COURSE LAID. ALL DAMAGED AREAS IN THE BINDER, BASE OR CURB AND GUTTER SHALL BE REPAIRED TO THE SATISFACTION OF THE OWNER PRIOR TO LAYING THE SURFACE COURSE. THE PAVING CONTRACTOR SHALL PROVIDE WHATEVER EQUIPMENT AND MANPOWER IS NECESSARY, INCLUDING THE USE OF POWER BROOMS TO PREPARE THE PAVEMENT FOR APPLICATION OF THE SURFACE COURSE. EQUIPMENT AND MANPOWER TO CLEAN PAVEMENT SHALL BE CONSIDERED INCIDENTAL TO THE COST OF THE CONTRACT. PRIME COAT ON THE BINDER COURSE SHALL BE CONSIDERED AS INCIDENTAL TO THE COST OF THE CONTRACT AND SHALL BE APPLIED TO THE BINDER AT A RATE OF 0.5 GALLONS PER SQUARE YARD.
6. CURING AND PROTECTION OF ALL EXPOSED CONCRETE SURFACES SHALL BE IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS.
7. SIDEWALKS SHALL BE OF THE THICKNESS AND DIMENSIONS AS SHOWN IN THE CONSTRUCTION PLANS. ALL SIDEWALKS CONCRETE SHALL DEVELOP A MINIMUM OF 3,500-PSI COMPRESSIVE STRENGTH AT 28 DAYS. CONTRACTION JOINTS SHALL BE SET AT 5' CENTERS, AND 3/4" PRE-MOLDED FIBER EXPANSION JOINTS SET AT 50' CENTERS AND WHERE THE SIDEWALK MEETS THE CURB, A BUILDING, OR ANOTHER SIDEWALK, OR AT THE END OF EACH POUR. ALL SIDEWALKS SHALL BE REINFORCED WITH THREE NO. 5 REINFORCING BARS (10' MINIMUM LENGTH). ALL SIDEWALKS CROSSING DRIVEWAYS SHALL BE A MINIMUM OF 6" THICK AND REINFORCED WITH 6X6 #6 WELDED WIRE MESH. ALL SIDEWALKS SHALL BE BROOM FINISHED. IF A MANHOLE FRAME FALLS WITHIN THE LIMITS OF A SIDEWALK, A BOX-OUT SECTION SHALL BE PLACED AROUND THE MANHOLE FRAME WITH A 3/4" EXPANSION JOINT.
8. BACKFILLING ALONG PAVEMENT SHALL BE THE RESPONSIBILITY OF THE EARTHWORK CONTRACTOR.
9. IT SHALL BE THE RESPONSIBILITY OF THE PAVING CONTRACTOR TO REMOVE FROM THE SITE ANY AND ALL MATERIAL AND DEBRIS, WHICH RESULTS FROM HIS CONSTRUCTION OPERATIONS AT NO ADDITIONAL EXPENSE TO THE OWNER.
10. TESTING OF THE SUB-BASE, BASE COURSE, BINDER COURSE, SURFACE COURSE AND CONCRETE WORK SHALL BE REQUIRED IN ACCORDANCE WITH THE "I.D.O.T. STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION" CURRENT EDITION, AND IN ACCORDANCE WITH THE SPECIFIC REQUIREMENTS OF THE GOVERNING MUNICIPALITY. A QUALIFIED TESTING FIRM SHALL BE EMPLOYED BY THE OWNER TO PERFORM THE REQUIRED TESTS.
11. PAINTED PAVEMENT MARKINGS AND SYMBOLS, OF THE TYPE AND COLOR AS NOTED ON THE CONSTRUCTION PLANS, SHALL BE INSTALLED IN ACCORDANCE WITH SECTION 7-502 OF SAME SPECIFICATIONS.
12. PAINTED PAVEMENT MARKINGS AND SYMBOLS SHALL BE INSTALLED ONLY WHEN THE AMBIENT AIR TEMPERATURE IS 40 DEGREES FAHRENHEIT AND THE FORECAST CALL FOR RISING TEMPERATURES.
13. ALL EXISTING CURB AND PAVEMENT SHALL BE PROTECTED DURING CONSTRUCTION, ANY DAMAGE TO THE CURB OR PAVEMENT WILL BE REPAIRED OR REPLACED AT NO ADDITIONAL COST TO THE OWNER.
14. ANY SIDEWALK THAT IS DAMAGED OR NOT ADA COMPLIANT, INCLUDING SIDEWALK RAMPS, MUST BE REPLACED PRIOR TO FINAL INSPECTION APPROVAL.


MANHOLE TYPE	INSIDE DIA.	MIN. WALL THICKNESS
A-4	4'-0"	5"
A-5	5'-0"	6"
A-6	6'-0"	7"




CATCHBASIN DETAIL
N.T.S.



3' DIA. TYPE B INLET
N.T.S.



TYPICAL CONCRETE PAVEMENT DETAIL



TYPICAL PAVEMENT DETAIL

PIPE DIA.	MIN. TRENCH WIDTH	MINIMUM RECOMMENDED COVER BASED ON VEHICLE LOADING CONDITIONS**			
INCHES	MILLIMETERS	H-25	H-20	(75T AXLE LOAD)	4*
4"	(100mm)	12"	12"	12"	4"
6"	(150mm)	18"	18"	18"	6"
8"	(200mm)	24"	24"	24"	8"
10"	(250mm)	30"	30"	30"	10"
12"	(300mm)	36"	36"	36"	12"
15"	(375mm)	45"	45"	45"	15"
18"	(450mm)	54"	54"	54"	18"
24"	(600mm)	72"	72"	72"	24"
30"	(750mm)	90"	90"	90"	30"
36"	(900mm)	108"	108"	108"	36"
42"	(1050mm)	126"	126"	126"	42"
48"	(1200mm)	144"	144"	144"	48"
60"	(1500mm)	180"	180"	180"	60"

RECOMMENDED MINIMUM TRENCH WIDTHS

PIPE DIA.	MIN. TRENCH WIDTH
4"	21"
6"	27"
8"	33"
10"	39"
12"	45"
15"	57"
18"	69"
24"	91"
30"	103"
36"	115"
42"	127"
48"	139"
60"	165"

MAXIMUM RECOMMENDED COVER BASED ON VEHICLE LOADING CONDITIONS


PIPE DIA.	CLASS I	CLASS II	CLASS III	CLASS III
INCHES	COMPACTED	DUMPED	95%	95%
4"	37"	18"	25"	18"
6"	54"	27"	38"	27"
8"	71"	36"	51"	36"
10"	88"	45"	64"	45"
12"	105"	54"	77"	54"
15"	131"	68"	95"	68"
18"	157"	82"	113"	82"
24"	212"	108"	151"	108"
30"	267"	134"	189"	134"
36"	322"	160"	227"	160"
42"	377"	186"	265"	186"
48"	432"	212"	303"	212"
60"	540"	270"	381"	270"

NOTES:

1. ALL PIPE SYSTEMS SHALL BE INSTALLED IN ACCORDANCE WITH ASTM D2321, "STANDARD PRACTICE FOR UNDERGROUND INSTALLATION OF THERMOPLASTIC PIPE FOR SEWERS AND OTHER GRAVITY FLOW APPLICATIONS", LATEST EDITION.
2. MEASURES SHOULD BE TAKEN TO PREVENT MIGRATION OF NATIVE FINES INTO BACKFILL MATERIAL WHEN REQUIRED.
3. FOUNDATION: WHERE THE TRENCH BOTTOM IS UNSTABLE, THE CONTRACTOR SHALL EXCAVATE TO A DEPTH REQUIRED BY THE ENGINEER AND REPLACE WITH SUITABLE MATERIAL AS SPECIFIED BY THE ENGINEER. AS AN ALTERNATIVE AND AT THE DISCRETION OF THE DESIGN ENGINEER, THE TRENCH BOTTOM MAY BE STABILIZED USING A GEOTEXTILE MATERIAL.
4. BEDDING: SUITABLE MATERIAL SHALL BE CLASS I, II OR III. THE CONTRACTOR SHALL PROVIDE DOCUMENTATION FOR MATERIAL SPECIFICATION TO ENGINEER. UNLESS OTHERWISE NOTED BY THE ENGINEER, MINIMUM BEDDING THICKNESS SHALL BE 4" (100mm) FOR 4"-24" (100mm-600mm), 6" (150mm) FOR 30"-60" (750mm-1500mm).
5. INITIAL BACKFILL: SUITABLE MATERIAL SHALL BE CLASS I, II OR III IN THE PIPE ZONE EXTENDING NOT LESS THAN 8" ABOVE GROUND OF PIPE. THE CONTRACTOR SHALL PROVIDE DOCUMENTATION FOR MATERIAL SPECIFICATION TO ENGINEER. MATERIAL SHALL BE INSTALLED AS REQUIRED IN ASTM D2321, LATEST EDITION.
6. MINIMUM COVER: MINIMUM COVER, H, IN NON-TRAFFIC APPLICATIONS (GRASS OR LANDSCAPE AREAS) IS 12" FROM THE TOP OF PIPE TO GROUND SURFACE. ADDITIONAL COVER MAY BE REQUIRED TO PREVENT FLOATION FOR TRAFFIC APPLICATIONS. MINIMUM COVER, H, IS 24" UP TO 48" DIAMETER PIPE AND 24" OF COVER FOR 60" DIAMETER PIPE, MEASURED FROM TOP OF PIPE TO BOTTOM OF FLEXIBLE PAVEMENT OR TO TOP OF RIGID PAVEMENT. FOR TRAFFIC APPLICATIONS WITH LESS THAN FOUR FEET OF COVER, EMBELEMMENT OF THE PIPE SHALL BE USING ONLY A CLASS I OR CLASS II BACKFILL.

ADVANCED DRAINAGE SYSTEMS, INC. (ADS) HAS PREPARED THIS DETAIL BASED ON INFORMATION PROVIDED TO ADS. THIS PROJECT IS INTENDED TO BE USED BY THE COMPONENTS AS REFERENCED AND HAS NOT PERFORMED ANY DESIGN SERVICES FOR THIS PROJECT. NOR HAS ADS INDEPENDENTLY VERIFIED THE INFORMATION SUPPLIED. THE INSTALLATION DETAILS PROVIDED HEREIN ARE GENERAL RECOMMENDATIONS AND ARE NOT SPECIFIC TO THIS PROJECT. THE DESIGN ENGINEER SHALL REVIEW THESE DETAILS PRIOR TO CONSTRUCTION. IT IS THE DESIGN ENGINEER'S RESPONSIBILITY TO ENSURE THE DETAILS PROVIDED HEREIN MEET OR EXCEED THE APPLICABLE STATE, OR LOCAL REQUIREMENTS AND TO ENSURE THE DETAILS PROVIDED HEREIN ARE ACCEPTABLE FOR THIS PROJECT.

DESIGNED BY: J. W. WILSON
CHECKED BY: J. W. WILSON
DATE: 09/28/17
PROJECT: 480 TRUMAN BLVD
LOCATION: HILLDALE, ILL 60138
DRAWING NUMBER: STD-101
DATE: 01/29/20
BY: JWW/02/YV/CMK
DATE: 01-01-88



PROJECT NO. 21 504 01
SCALE: NTS
DATE: NOV 15, 2021

FIGURE: 402.03
SHEET 1 OF 1

TEBRUGGE ENGINEERING
410 E. CHURCH STREET - SUITE A • SANDWICH, IL 60548
PHONE: (815) 786-0195 | TEBRUGGEENGINEERING.COM


PREPARED FOR:
TMF PLASTIC SOLUTIONS, LLC
12127 GALENA RD-UNIT B, PLANO, IL 60545

TMF PLASTIC BUILDING ADDITION
GENERAL NOTES & DETAILS

PROJECT NO. 21 504 01
SCALE: NTS
DATE: NOV 15, 2021

FIGURE: 402.03
SHEET 1 OF 1

SHEET NO. **5**
OF 5 SHEETS



Luminaire Schedule - Part numbers are provided by the manufacturer and are only intended to be used as a reference to output and optics used.										
Symbol	Qty	Tag	Arrangement	Lum. Watts	Arr. Watts	Lum. Lumens	Arr. Lum. Lumens	LLF	Manufacturer	Description
☐	2	WP	Single	29.1	29.1	3060	3060	0.900	HUBBELL OUTDOOR LIGHTING	SG1-30-4K7-FT

Calculation Summary								
Label	CalcType	Units	Avg	Max	Min	Avg/Min	Max/Min	
SITE_Planar	Illuminance	Fc	0.46	5.0	0.0	N.A.	N.A.	

Luminaire Location Summary				
LumNo	Label	Mtg Ht	Orient	Tilt
1	SG1-30-4K7-FT	13	256	0
2	SG1-30-4K7-FT	13	256	0

Lighting applications and designs are provided by the recipient of this document. We make no warranty as to the completeness, accuracy or reliability of the information provided. PG-Enlighten is not responsible for any errors or omissions in this document. PG-Enlighten is not a lighting design firm. PG-Enlighten is a lighting design consultant. PG-Enlighten is not a lighting design engineer. PG-Enlighten is not a lighting design architect. PG-Enlighten is not a lighting design contractor. PG-Enlighten is not a lighting design installer. PG-Enlighten is not a lighting design manufacturer. PG-Enlighten is not a lighting design distributor. PG-Enlighten is not a lighting design wholesaler. PG-Enlighten is not a lighting design retailer. PG-Enlighten is not a lighting design dealer. PG-Enlighten is not a lighting design agent. PG-Enlighten is not a lighting design broker. PG-Enlighten is not a lighting design intermediary. PG-Enlighten is not a lighting design facilitator. PG-Enlighten is not a lighting design provider. PG-Enlighten is not a lighting design provider of services. PG-Enlighten is not a lighting design provider of products. PG-Enlighten is not a lighting design provider of information. PG-Enlighten is not a lighting design provider of data. PG-Enlighten is not a lighting design provider of software. PG-Enlighten is not a lighting design provider of hardware. PG-Enlighten is not a lighting design provider of equipment. PG-Enlighten is not a lighting design provider of materials. PG-Enlighten is not a lighting design provider of components. PG-Enlighten is not a lighting design provider of parts. PG-Enlighten is not a lighting design provider of accessories. PG-Enlighten is not a lighting design provider of peripherals. PG-Enlighten is not a lighting design provider of add-ons. PG-Enlighten is not a lighting design provider of upgrades. PG-Enlighten is not a lighting design provider of enhancements. PG-Enlighten is not a lighting design provider of improvements. PG-Enlighten is not a lighting design provider of optimizations. PG-Enlighten is not a lighting design provider of refinements. PG-Enlighten is not a lighting design provider of adjustments. PG-Enlighten is not a lighting design provider of modifications. PG-Enlighten is not a lighting design provider of alterations. PG-Enlighten is not a lighting design provider of changes. PG-Enlighten is not a lighting design provider of updates. PG-Enlighten is not a lighting design provider of patches. PG-Enlighten is not a lighting design provider of releases. PG-Enlighten is not a lighting design provider of versions. PG-Enlighten is not a lighting design provider of editions. PG-Enlighten is not a lighting design provider of builds. PG-Enlighten is not a lighting design provider of packages. PG-Enlighten is not a lighting design provider of distributions. PG-Enlighten is not a lighting design provider of installations. PG-Enlighten is not a lighting design provider of deployments. PG-Enlighten is not a lighting design provider of rollouts. PG-Enlighten is not a lighting design provider of launches. PG-Enlighten is not a lighting design provider of introductions. PG-Enlighten is not a lighting design provider of presentations. PG-Enlighten is not a lighting design provider of demonstrations. PG-Enlighten is not a lighting design provider of showcases. PG-Enlighten is not a lighting design provider of exhibitions. PG-Enlighten is not a lighting design provider of events. PG-Enlighten is not a lighting design provider of conferences. PG-Enlighten is not a lighting design provider of seminars. PG-Enlighten is not a lighting design provider of workshops. PG-Enlighten is not a lighting design provider of webinars. PG-Enlighten is not a lighting design provider of podcasts. PG-Enlighten is not a lighting design provider of newsletters. PG-Enlighten is not a lighting design provider of magazines. PG-Enlighten is not a lighting design provider of newspapers. PG-Enlighten is not a lighting design provider of journals. PG-Enlighten is not a lighting design provider of books. PG-Enlighten is not a lighting design provider of manuals. PG-Enlighten is not a lighting design provider of guides. PG-Enlighten is not a lighting design provider of whitepapers. PG-Enlighten is not a lighting design provider of reports. PG-Enlighten is not a lighting design provider of studies. PG-Enlighten is not a lighting design provider of analyses. PG-Enlighten is not a lighting design provider of evaluations. PG-Enlighten is not a lighting design provider of assessments. PG-Enlighten is not a lighting design provider of audits. PG-Enlighten is not a lighting design provider of reviews. PG-Enlighten is not a lighting design provider of ratings. PG-Enlighten is not a lighting design provider of rankings. PG-Enlighten is not a lighting design provider of comparisons. PG-Enlighten is not a lighting design provider of benchmarks. PG-Enlighten is not a lighting design provider of standards. PG-Enlighten is not a lighting design provider of best practices. PG-Enlighten is not a lighting design provider of case studies. PG-Enlighten is not a lighting design provider of testimonials. PG-Enlighten is not a lighting design provider of references. PG-Enlighten is not a lighting design provider of letters of intent. PG-Enlighten is not a lighting design provider of contracts. PG-Enlighten is not a lighting design provider of agreements. PG-Enlighten is not a lighting design provider of memorandums. PG-Enlighten is not a lighting design provider of minutes. PG-Enlighten is not a lighting design provider of resolutions. PG-Enlighten is not a lighting design provider of policies. PG-Enlighten is not a lighting design provider of procedures. PG-Enlighten is not a lighting design provider of protocols. PG-Enlighten is not a lighting design provider of guidelines. PG-Enlighten is not a lighting design provider of templates. PG-Enlighten is not a lighting design provider of forms. PG-Enlighten is not a lighting design provider of documents. PG-Enlighten is not a lighting design provider of records. PG-Enlighten is not a lighting design provider of archives. PG-Enlighten is not a lighting design provider of databases. PG-Enlighten is not a lighting design provider of systems. PG-Enlighten is not a lighting design provider of networks. PG-Enlighten is not a lighting design provider of servers. PG-Enlighten is not a lighting design provider of clients. PG-Enlighten is not a lighting design provider of devices. PG-Enlighten is not a lighting design provider of applications. PG-Enlighten is not a lighting design provider of services. PG-Enlighten is not a lighting design provider of products. PG-Enlighten is not a lighting design provider of solutions. PG-Enlighten is not a lighting design provider of offerings. PG-Enlighten is not a lighting design provider of programs. PG-Enlighten is not a lighting design provider of initiatives. PG-Enlighten is not a lighting design provider of projects. PG-Enlighten is not a lighting design provider of campaigns. PG-Enlighten is not a lighting design provider of promotions. PG-Enlighten is not a lighting design provider of advertisements. PG-Enlighten is not a lighting design provider of public relations. PG-Enlighten is not a lighting design provider of social media. PG-Enlighten is not a lighting design provider of content marketing. PG-Enlighten is not a lighting design provider of search engine optimization. PG-Enlighten is not a lighting design provider of email marketing. PG-Enlighten is not a lighting design provider of direct marketing. PG-Enlighten is not a lighting design provider of experiential marketing. PG-Enlighten is not a lighting design provider of cause marketing. PG-Enlighten is not a lighting design provider of community marketing. PG-Enlighten is not a lighting design provider of partnership marketing. PG-Enlighten is not a lighting design provider of affiliate marketing. PG-Enlighten is not a lighting design provider of referral marketing. PG-Enlighten is not a lighting design provider of influencer marketing. PG-Enlighten is not a lighting design provider of sponsorship marketing. PG-Enlighten is not a lighting design provider of event marketing. PG-Enlighten is not a lighting design provider of trade show marketing. PG-Enlighten is not a lighting design provider of industry conference marketing. PG-Enlighten is not a lighting design provider of trade journal marketing. PG-Enlighten is not a lighting design provider of trade magazine marketing. PG-Enlighten is not a lighting design provider of trade newspaper marketing. PG-Enlighten is not a lighting design provider of trade website marketing. PG-Enlighten is not a lighting design provider of trade directory marketing. PG-Enlighten is not a lighting design provider of trade association marketing. PG-Enlighten is not a lighting design provider of trade organization marketing. PG-Enlighten is not a lighting design provider of trade group marketing. PG-Enlighten is not a lighting design provider of trade network marketing. PG-Enlighten is not a lighting design provider of trade community marketing. PG-Enlighten is not a lighting design provider of trade ecosystem marketing. PG-Enlighten is not a lighting design provider of trade environment marketing. PG-Enlighten is not a lighting design provider of trade landscape marketing. PG-Enlighten is not a lighting design provider of trade ecosystem marketing. PG-Enlighten is not a lighting design provider of trade environment marketing. PG-Enlighten is not a lighting design provider of trade landscape marketing.



#	Date	Comments

Drawn By: Joeli Collins
 Drawn By: joeli.collins@pg-enlighten.com
 Date: 11/18/2021
 Scale: 1" = 8'

Project Name:
TMF PLASTIC SOLUTIONS
 Location:
 12127 GALENA RD UNIT B, PLANO, IL

SLING Series

SLENDER WALLPACK

tradeSELECT™

FEATURES

- Two sizes for a variety of applications
- Ranges from 21W to 80W with up to 8000 lumens
- SG1 Series replaces from 100W-150W HID; SG2 Series replaces from 150W-250W HID
- Comfort lens available as an option or accessory provides glare control and enhanced uniformity
- Knuckle and trunnion accessory mounting kits available for flood applications
- IP65 and certified to UL 1598 for use in wet locations up to 40°C ambient
- DLC (DesignLights Consortium Qualified - see www.designlights.org)



RELATED PRODUCTS

- Ø [LNC Litepak](#)
- Ø [LNC2 Litepak](#)
- Ø [LNC3 Litepak](#)
- Ø [LNC4 Litepak](#)
- Ø [GeoPak](#)
- Ø [GeoPak2](#)



*3000K and warmer CCTs only

SPECIFICATIONS

HOUSING

- Rugged die-cast aluminum housing with corrosion resistant powder coat finish
- Heating dissipating fins provide superior thermal performance extending the life of the electronic components
- Impact resistant tempered glass offers zero uplight
- Comfort lens available as an option or accessory to reduce glare (7-10% lumen reduction) and provide better uniformity

OPTICS

- 3000K, 4000K and 5000K CCT nominal with 70 CRI
- Smaller SG1 housing has 2 LEDs, larger SG2 housing has 3 LEDs

INSTALLATION

- Side hinge allows for easy installation and wiring
- Side movement avoids damage to the lens and helps prevent injury common in drop down hinge designs
- Mounts to 4" junction box and includes a gasket to help seal electrical connections
- Four 1/2" threaded conduits hubs for surface conduit provided

ELECTRICAL

- 120-277V, 50/60Hz electronic drivers
- 347V and 480V available in large SG2 housing
- 10KA surge protection included

OPTIONS/CONTROLS

- Button photocontrol for dusk to dawn energy savings. Stock versions include 120V-277V PC with a cover which provides a choice to engage photocontrol or not. PC is installed in top hub
- Occupancy sensor available for on/off and dimming control in larger SG2 housing
- SiteSync™ wireless lighting control delivers flexible control strategies for reducing power consumption and minimizing maintenance costs while delivering the right light levels with a simple and affordable wireless solution. See ordering information or visit www.hubbellighting.com/sitesync for more details
- Battery backup options available in larger SG2 housing rated for either 0° C or -30° C. Performance exceeds NEC requirement providing 1fc minimum over 10'x10' at 11' mounting height

CERTIFICATIONS

- DesignLights Consortium® (DLC) qualified. Please refer to the DLC website for specific product qualifications at www.designlights.org
- Listed to UL1598 for use in wet location, listed for -40°C to 40°C applications
- IDA approved with zero uplight for 3000K and warmer CCTs
- IP65

WARRANTY

- 5 year limited warranty
- See [HLI Standard Warranty](#) for additional information

KEY DATA	
Lumen Range	2263-8079
Wattage Range	21-80
Efficacy Range (LPW)	101-113
Fixture Projected Life (Hours)	L70>50K
Weights lbs. (kg)	4.3-11 (2.0-5.0)

SLING SERIES

SLENDER WALLPACK

ORDERING GUIDE

Example: SG1-20-3K7-FT-UNV-DBT-PCU-CS

CATALOG # _____

ORDERING INFORMATION

Housing	CCT/CRI	Distribution	Voltage	Color/Finish	Control Options	Options
SG1-10 Size 1, 10W	3K7 3000K, 70 CRI	FT Fwd Throw	UNV 120V-277V	BLT Black Matte Textured	PCU Universal Button Photocontrol (120-277V)	CS Comfort Lens
SG1-20 Size 1, 20W	4K7 4000K, 70 CRI		120 120V	BLS Black Gloss Smooth	SCP ^{1,2,3} Occupancy Sensor Programmable (Dim)	E ^{1,2} Battery 0°C
SG1-30 Size 1, 30W	5K7 5000K, 70 CRI		277 277V	DBT Dark Bronze Matte Textured	SWP ^{1,2} SiteSync Pre-commission	EH ^{1,2} Battery w/ heater -20°
SG1-40 Size 1, 40W			UHV 347V-480V	DBS Dark Brone Gloss Smooth	SWPM ^{1,2} SiteSync Pre-commission w/ Sensor	
SG2-50 Size 2, 50W				GTT Graphite Matte Textured	Specify MTG HT for SCO/SCP & SWPM	
SG2-80 Size 2, 80W				LGS Light Grey Gloss Smooth	8F Up to 8'	
				PSS Platinum Silver Smooth	20F Up to 20'	
				WHT White Matte Textured		
				WHS White Gloss Smooth		
				VGT Verde Green Textured		
				Color Option		
				CC Custom Color		

Notes:

- 1 Available in SG2 only, UHV available in SG2-50 only
- 2 Sensor controls & battery backup can not be used with flood accessory or kit or for inverted/up mounting, 120-277V only for SCO/SCP, 120 or 277 only for SWP, SWPM, E & EH
- 3 Must order minimum of one remote control to program dimming settings, 0-10V fully adjustable dimming with automatic daylight calibration and different time delay settings, 120-277V only

STOCK ORDERING INFORMATION

Catalog Number	CCT/CRI	Wattage	Mounting Height	Color	Color	Delivered Lumens	LPW	Weight lbs. (kg)
SG1-10-PCU	5000K/70	11W	8-12ft	120-277V	Dark Bronze	1349	122	4.3 (2.0)
SG1-10-4K-PCU	4000K/70	11W	8-12ft	120-277V	Dark Bronze	1424	129	4.3 (2.0)
SG1-20-PCU	5000K/70	21W	8-12ft	120-277V	Dark Bronze	2263	108	4.3 (2.0)
SG1-20-4K-PCU	4000K/70	21W	8-12ft	120-277V	Dark Bronze	2310	110	4.3 (2.0)
SG1-30-PCU	5000K/70	29W	10-15ft	120-277V	Dark Bronze	3270	113	4.3 (2.0)
SG1-30-4K-PCU	4000K/70	29W	10-15ft	120-277V	Dark Bronze	3060	105	4.3 (2.0)
SG1-40-PCU	5000K/70	38W	10-15ft	120-277V	Dark Bronze	4008	105	4.3 (2.0)
SG1-40-4K-PCU	4000K/70	38W	10-15ft	120-277V	Dark Bronze	4070	106	4.3 (2.0)
SG2-50-PCU	5000K/70	51W	12-18ft	120-277V	Dark Bronze	5548	110	11 (5.0)
SG2-50-4K-PCU	4000K/70	51W	12-18ft	120-277V	Dark Bronze	5526	109	11 (5.0)
SG2-80-PCU	5000K/70	80W	15-25ft	120-277V	Dark Bronze	8061	101	11 (5.0)
SG2-80-4K-PCU	4000K/70	80W	15-25ft	120-277V	Dark Bronze	8079	101	11 (5.0)

SLING SERIES

SLENDER WALLPACK

ORDERING GUIDE

OPTIONS AND ACCESSORIES

Catalog Number	Description	Weight lbs. (kg)
<input type="checkbox"/> SG1-CS	Acrylic comfort lens for SG1	1 (45)
<input type="checkbox"/> SG2-CS	Acrylic comfort lens for SG2	1 (45)
<input type="checkbox"/> SG1-YOKE	SG1 Series Yoke/Floodlight mount kit, includes visor	2.0 (1.0)
<input type="checkbox"/> SG1-KNUCKLE	SG1 Series Knuckle/Floodlight mount kit, includes visor	2.0 (1.0)
<input type="checkbox"/> SG2-YOKE	SG2 Series Yoke/Floodlight mount kit, includes visor	2.0 (1.0)
<input type="checkbox"/> SG2-KNUCKLE	SG2 Series Knuckle/Floodlight mount kit, includes visor	2.0 (1.0)
<input type="checkbox"/> SCP-REMOTE*	Remote control for SCP option. Order at least one per project to program and control fixtures	1 (45)
<input type="checkbox"/> SG1-SPC	Vandal Resistant Lens (shield polycarbonate), SG1	3 (1.5)
<input type="checkbox"/> SG2-SPC	Vandal Resistant Lens (shield polycarbonate), SG2	3 (1.5)
<input type="checkbox"/> SG1-WCP	Universal Wall Cover Plate, Dark Bronze, SG1	10 (5)
<input type="checkbox"/> SG2-WCP-H	Horizontal Mount Wall Cover Plate, Dark Bronze, SG2	10 (5)
<input type="checkbox"/> SG2-WCP-V	Vertical Mount Wall Cover Plate, Dark Bronze, SG2	10 (5)
<input type="checkbox"/> SG2XL-WCP-H	Horizontal Mount Wall Cover Plate, DB, SG2 with battery or sensor	10 (5)
<input type="checkbox"/> SG2XL-WCP-V	Vertical Mount Wall Cover Plate, DB, SG2 with battery or sensor	10 (5)

ACCESSORIES AND SERVICES (ORDERED SEPARATELY)

Control Options	
SWUSB¹	SiteSync™ interface software loaded on USB flash drive for use with owner supplied PC (Windows based only). Includes SiteSync™ license, software and USB radio bridge node.
SWTAB¹	Windows tablet and SiteSync™ interface software. Includes tablet with preloaded software, SiteSync™ license and USB radio bridge node.
SWBRG²	SiteSync™ USB radio bridge node only. Order if a replacement is required or if an extra bridge node is requested.

Notes:

- When ordering SiteSync™ at least one of these two interface options must be ordered per project.
- If needed, an additional Bridge Node can be ordered.

SLING SERIES

SLENDER WALLPACK

PERFORMANCE DATA

Description	# of LEDs	Drive Current	System Watts	5K (5000K NOMINAL 70 CRI)					4K (4000K NOMINAL 70 CRI)					3K (3000K NOMINAL 80 CRI)				
				Lumens	LPW	B	U	G	Lumens	LPW	B	U	G	Lumens	LPW	B	U	G
SG1-10	2	140mA	11	1349	122	1	0	0	1424	129	1	0	0	1003	91	1	0	0
SG1-20	2	250mA	21	2449	115	1	0	0	2310	110	1	0	0	2054	95	1	0	0
SG1-30	2	350mA	29	3332	117	2	0	0	3060	106	1	0	0	2913	100	1	0	0
SG-40	2	450mA	38	4008	105	2	0	0	4070	106	2	0	0	3845	100	2	0	0
SG2-50-UHV	3	350mA	44	4633	106	2	0	0	4609	105	2	0	0	3895	90	2	0	0
SG2-50	3	415mA	51	5548	109	2	0	0	5526	107	2	0	0	4700	92	2	0	0
SG2-80	3	650mA	80	7851	98	2	0	1	8079	103	2	0	1	6721	86	2	0	1

*347 and 480 VAC input Lumen values are from photometric test performed in accordance with IESNA LM-79-08. Data is considered to be representative of the configurations shown. Actual performance may differ as a result of end-user environment application and inherent performance balances of the electrical components.

ELECTRICAL DATA

Catalog number	# of Drivers	Input Voltage	Current (AMPS)	System Power
SG1-10	1	120	0.09	11.0
	1	277	0.04	11.0
SG1-20	1	120	0.18	21.0
	1	277	0.08	21.0
SG1-30	1	120	0.24	28.9
	1	277	0.10	28.9
SG2-40	1	120	0.32	38.3
	1	277	0.14	38.3
SG-50-UHV	1	347	0.13	43.5
	1	480	0.18	43.5
SG2-50	1	120	0.42	50.6
	1	277	0.18	50.6
SG2-80	1	120	0.68	79.8
	1	277	0.29	79.8

PROJECTED LUMEN MAINTENANCE

Ambient Temperature	OPERATING HOURS					
	0	25,000	50,000	TM-21-11 ¹ L96 60,000	100,000	L70 (Hours)
25°C / 77°F	1.00	0.98	0.97	0.96	0.95	>791,000
40°C / 104°F	0.99	0.98	0.96	0.96	0.94	>635,000

1. Projected per IESNA TM-21-11¹ (Nichia 219B, 700mA, 85°C Ts, 10,000hrs) Data references the extrapolated performance projections for the base model in a 40°C ambient, based on 10,000 hours of LED testing per IESNA LM-80-08

SLING SERIES



SLENDER WALLPACK

LUMINAIRE AMBIENT TEMPERATURE FACTOR (LATF)



Ambient Temperature		Lumen Multiplier
0° C	32° F	1.02
10° C	50° F	1.01
20° C	68° F	1.00
25° C	77° F	1.00
30° C	86° F	1.00
40° C	104° F	0.99
50° C	122° F	0.96

Use these factors to determine relative lumen output for average ambient temperatures from 0-40°C (32-104°F).

DIMENSIONS





A	B	C	Weight
4.19" (107mm)	7.80" (198mm)	6.61" (168mm)	4.4lbs (2kg)



A	B	C	Weight
5.80" (147mm)	11.14" (283mm)	9.52" (242mm)	11lbs (5kg)

SG2 with occupancy sensor and battery options



A	B	C	Weight
7.26" (184mm)	13.84" (352mm)	9.52" (242mm)	11lbs (5kg)

SLING SERIES

SLENDER WALLPACK

PHOTOMETRY

SG1-10-4K7


LUMINAIRE DATA

Description	4000 Kelvin, 70 CRI
Distribution Type	Forward Throw
Delivered Lumens	1424
Watts	11.4
Efficacy	125
Mounting	Wall

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
Downward Street Side	996.6	70.0
Downward House Side	427.8	30.0
Downward Total	1424.4	100.0
Upward Street Side	0.0	0.0
Upward House Side	0.0	0.0
Upward Total	0.0	0.0
Total Flux	1424.4	100.0

ISOMETRIC FOOTCANDLE



SG1-20-4K7


LUMINAIRE DATA

Description	4000 Kelvin, 70 CRI
Distribution Type	Forward Throw
Delivered Lumens	2310
Watts	20.9
Efficacy	111
Mounting	Wall

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
Downward Street Side	1618	70.0
Downward House Side	692.1	30.0
Downward Total	2310.1	100.0
Upward Street Side	0.0	0.0
Upward House Side	0.0	0.0
Upward Total	0.0	0.0
Total Flux	2310.3	100.0

ISOMETRIC FOOTCANDLE



SG1-30


LUMINAIRE DATA

Description	4000 Kelvin, 70 CRI
Distribution Type	Forward Throw
Delivered Lumens	3060
Watts	29.1
Efficacy	105
Mounting	Wall

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
Downward Street Side	2619.4	70.9
Downward House Side	890.4	29.1
Downward Total	3059.8	100.0
Upward Street Side	0.0	0.0
Upward House Side	0.0	0.0
Upward Total	0.0	0.0
Total Flux	3059.8	100.0

ISOMETRIC FOOTCANDLE



SLING SERIES

SLENDER WALLPACK

PHOTOMETRY

SG1-40-4K7


LUMINAIRE DATA

Description	4000 Kelvin, 70 CRI
Distribution Type	Foward Throw
Delivered Lumens	4070
Watts	38.1
Efficacy	107
Mounting	Wall

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
Downward Street Side	2857.7	70.2
Downward House Side	1215.5	29.8
Downward Total	4070.2	100.0
Upward Street Side	0.0	0.0
Upward House Side	0.0	0.0
Upward Total	0.0	0.0
Total Flux	4070.2	100.0

ISOMETRIC FOOTCANDLE



SG2-50-4K7


LUMINAIRE DATA

Description	4000 Kelvin, 70 CRI
Distribution Type	Foward Throw
Delivered Lumens	5525.7
Watts	51.7
Efficacy	107
Mounting	Wall

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
Downward Street Side	4611.8	83.5
Downward House Side	913.9	16.5
Downward Total	5525.7	100.0
Upward Street Side	0.0	0.0
Upward House Side	0.0	0.0
Upward Total	0.0	0.0
Total Flux	5525.7	100.0

ISOMETRIC FOOTCANDLE



SG2-80-4K7


LUMINAIRE DATA

Description	4000 Kelvin, 70 CRI
Distribution Type	Foward Throw
Delivered Lumens	8453
Watts	78.5
Efficacy	108
Mounting	Wall

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
Downward Street Side	6677.7	79.0
Downward House Side	1775.5	21.0
Downward Total	8453.2	100.0
Upward Street Side	0.0	0.0
Upward House Side	0.0	0.0
Upward Total	0.0	0.0
Total Flux	8453.2	100.0

ISOMETRIC FOOTCANDLE



SLING SERIES


SLENDER WALLPACK

ADDITIONAL INFORMATION

Shipping Information

Catalog Number	G.W(kg)/ CTN	Carton Dimensions			Carton Qty. per Master Pack	Pallet Qty.
		Length Inch (cm)	Width Inch (cm)	Height Inch (cm)		
SG1	4.35lbs (2kg)	9.5 (24)	8.25 (21)	5.25 (13)	6	98
SG2	11lbs (5kg)	14 (36)	11.5 (29)	8 (20)	2	64

Accessories and Services




Acrylic comfort lens provides glare control, improved visual comfort and better uniformity



Visor accessory included with mounting accessory kits





Flood mounting accessories - 1/2" threaded knuckle or yoke (includes grommet and 3' SO cord)




Photocontrol option available for energy-saving dusk-to-dawn operation




Side hinged for easy installation and wiring access, single screw secures housing closure



SG(X)-PMA-(X)-XX




SG(X)-WCP-H



SG(X)-WCP-V

Features




Battery back up feature with side indicator.

Exceeds Life Safety Code average illuminance of 1.0 fc. at 12' mounting height. Assumes open space with no obstructions. Battery backup units consume 6W when charging a dead battery and 2W during maintenance charging. EH (units with a heater) consume up to an additional 8W when charging if the battery temp is lower than 10°C


Diagrams for illustration purposes only, please consult factory for application layout.




SiteSync™ Lighting Control delivers flexible control strategies for reducing power consumption and minimizing maintenance costs while delivering the right light levels with a simple and affordable wireless solution.




WEST ELEVATION



SOUTH ELEVATION



NORTH ELEVATION



EAST ELEVATION

TMF MANAGEMENT
 12127B GALENA ROAD
 KENDALL COUNTY, ILLINOIS

STEVEN W. HANSEN, ARCHITECT
 880 LONGVIEW COURT
 SUGAR GROVE, IL.
 630-204-8613 - 60554

REV. #	DATE	DESCRIPTION
1	10-25-2021	SCHEME 2 10-25-2021
2	11-10-2021	SCHEME 2 11-10-2021

PROJECT NO.

SK3.1



TEBRUGGE ENGINEERING

410 E. CHURCH ST.—SUITE A
SANDWICH, IL 60548

PHONE: (815) 786-0195
EMAIL: INFO@TEBRUGGEENGINEERING.COM
WEBSITE: WWW.TEBRUGGEENGINEERING.COM

November 23, 2021

Mr. Matt Asselmeier
Kendall County Planning, Building and Zoning Department
111 W Fox St
Room 204
Yorkville, IL 60560-1498

Re: TMF Plastic Building Addition
12127 Galena Rd – Unit B
Plano, IL

Dear Mr. Asselmeier,

We have completed the revisions per your review letter received on 11.23.21. A copy of the revised Civil Site Plans and Final Plan is enclosed.

1. The zip code was corrected.
2. We did find that there were two signs in the parking lot, so we added a second striped handicap stall.
3. The north doors do not require any access drive.
4. The facility runs 3 shifts and has 32 employees per shift. There are no company vehicles.
5. We have added a 6' chain link fence with vinyl slats along the east property line in front of the docks.
6. The back area near the docks acts as a loading berth.
7. Side and rear yard setbacks are detailed off the corners of the building. The setbacks meet the M-I zoning requirement.
8. There is no mechanical equipment on the roof. No HVAC on this building addition.
9. The lighting levels at the property line meet the 0.2 requirements.
10. The addition does not need any refuse containers.

If you have any additional questions, please contact us.

Sincerely,

Tebrugge Engineering

A handwritten signature in black ink is written over a solid black rectangular redaction box.

John Tebrugge