

KENDALL COUNTY HIGHWAY DEPARTMENT

NOTICE TO BIDDERS CONDITIONS / SPECIFICATIONS BID FORM

For

Tandem Axle Cab & Chassis

November 8, 2024

Notice to Bidders

Kendall County Highway Department is accepting sealed bids for the purchase of a new tandem axle cab & chassis. Specifications, conditions and bid forms are available at the Highway Department Office, 6780 Route 47, Yorkville, IL 60560. The bid opening will be on November 8, 2024 at 10:00 AM. Additional information may be obtained by calling (630) 553-7616.

CONDITIONS

- 1. Bids shall be made upon the form(s) provided and all blank spaces in the form(s) shall be fully completed in ink. Signatures shall be in long hand and the completed form shall be without delineations, alterations, or erasures. Bids shall be submitted in a sealed envelope marked "Truck Cab & Chassis" to Kendall County Highway Department, 6780 Route 47, Yorkville, IL 60560 by 10:00 A.M. on November 8, 2024.
- 2. Specifications provided in this bid document are minimum required specifications. Bidder shall submit with their bid a listing of all specifications that do not comply with the minimum specifications listed.
- 3. The successful bidder shall deliver the new cab & chassis, all attachments, appurtenances and documentation to the Highway Department at no additional cost to the Highway Department. Bidders are advised to include any transportation costs in their base bid.
- 4. The bidder certifies that they shall deliver the new tandem axle cab & chassis to Kendall County Highway Department by <u>November 29, 2024</u>.
- 5. Successful bidder shall supply Kendall County Highway Department with an owner's manual for the truck at no cost to the Department.
- 6. All standard manufacturers' warranties and any dealer extended warranties shall apply to the purchase of the new truck, as detailed in the Specifications included herein.
- 7. Kendall County reserves the right to reject any or all bids, to waive any irregularities in the bids, and to accept in whole or in part such bid or bids as may be deemed to be in the best interest of Kendall County.

SPECIFICATIONS

	Description
Price Level	
	WST 47X/49X PRL-28X (EFF:MY25 ORDERS)
Data Version	
	SPECPRO21 DATA RELEASE VER 013
Vehicle Configur	ation
and the second	WESTERN STAR 47X
	2025 MODEL YEAR SPECIFIED
	SET FORWARD AXLE - TRUCK
	TRAILER TOWING PROVISION AT END OF FRAME WITH SAE J560
	LH PRIMARY STEERING LOCATION
General Service	
	TRUCK/TRAILER CONFIGURATION
	DOMICILED, USA (EXCLUDING CALIFORNIA AND CARB OPT-IN STATES)
	EPA EMISSIONS CERTIFICATION FOR REGISTRATION IN EPA OR ACT STATES - EPA CLEAN IDLE (INCLUDES 6X4 INCH LABEL ON LOWER FORWARD OF DRIVER DOOR)
	UTILITY/REPAIR/MAINTENANCE SERVICE
	GOVERNMENT BUSINESS SEGMENT
	DIRT/SAND/ROCK COMMODITY
	TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS
	MAXIMUM 8% EXPECTED GRADE
	SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE
	WESTERN STAR VOCATIONAL WARRANTY
	EXPECTED FRONT AXLE(S) LOAD : 18000.0 lbs

ED REAR DRIVE AXLE(S) LOAD :
ED GROSS VEHICLE WEIGHT CAPACITY
ED GROSS COMBINATION WEIGHT :
LOW/END DUMP BODY
1) TRAILER
70 HP @ 2100 RPM; 2100 GOV RPM, T @ 1200 RPM
ROAD SPEED LIMIT
CONTROL SPEED LIMIT SAME AS ROAD MIT
SING OF AFTERTREATMENT ENABLED ODE-CLEANS HYDROCARBONS AT /IPERATURES ONLY
ASH SWITCH, ROLLING ENGAGEMENT E IN NEUTRAL), BEFORE DRIVING
/GHG 2024 CONFIGURATION
RD OIL PAN
NOUNTED OIL CHECK AND FILL
HOOD AIR INTAKE WITH ENGINE D AIR CLEANER, WITH UTSIDE AIR AND SNOW DOOR
60 AMP 28-SI QUADRAMOUNT PAD TOR WITH REMOTE BATTERY VOLT
GENUINE, HIGH TEMP AGM STARTING LING, MIN 2775CCA, 570RC, D STUD BATTERIES
GER SEAT BATTERY BOX VENTED TO OF CAB
BOX MOUNTED UNDER PASSENGER
OUND RETURN FOR BATTERY CABLES DITIONAL FRAME GROUND RETURN

Description PLASTIC BATTERY BOX COVER
NON-ESSENTIAL POSITIVE LOAD DISCONNECT, IN CAB CONTROL SWITCH MOUNTED OUTBOARD OF DRIVER SEAT
POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER
CUMMINS TURBOCHARGED 18.7 CFM AIR COMPRESSOR WITH INTERNAL SAFETY VALVE
ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM
C-BRAKE BY JACOBS WITH LOW/OFF/HIGH BRAKING DASH SWITCH
RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE
ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH
11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTEM HEIGHT
RH CURVED VERTICAL TAILPIPE B-PILLAR MOUNTED ROUTED FROM STEP
13 GALLON DIESEL EXHAUST FLUID TANK
UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER
LH HEAVY DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION
STANDARD DIESEL EXHAUST FLUID TANK CAP
STAINLESS STEEL AFTERTREATMENT DEVICE/MUFFLER/TAILPIPE SHIELD
AIR POWERED ON/OFF ENGINE FAN CLUTCH
AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH, NON ENGINE MOUNTED
DETROIT FUEL/WATER SEPARATOR WITH WATER IN FUEL SENSOR
CUMMINS SPIN ON FUEL FILTER
FULL FLOW OIL FILTER
1400 SQUARE INCH VOCATIONAL RADIATOR
ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE) EXTENDED LIFE COOLANT
GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT

	Description	
	STANDARD CHARGE AIR COOLER PLUMBING	
	RADIATOR DRAIN VALVE	
	LOWER RADIATOR GUARD	
	ELECTRIC GRID AIR INTAKE WARMER	
	DELCO 12V 39MT HD/OCP STARTER WITH THERMAL PROTECTION AND INTEGRATED MAGNETIC SWITCH	
ransmission		
	ALLISON 3000 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION	
ransmission Eq	uipment	
en de la chiad	ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS, HS, MH AND TRV	
	ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES	
	PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY	
	SECONDARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY	
	S5 PERFORMANCE LIMITING PRIMARY SHIFT SCHEDULE, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY	
	S5 PERFORMANCE LIMITING SECONDARY SHIFT SCHEDULE, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY	
	2100 RPM PRIMARY MODE SHIFT SPEED	
	2100 RPM SECONDARY MODE SHIFT SPEED	
	MAXIMUM OUTPUT SPEED FOR PTO ENGAGEMENT 2100 RPM	
	QUICKFIT BODY LIGHTING CONNECTOR UNDER CAB, WITH BLUNTCUTS	
	NO AUX/ACC TRANSMISSION WIRING	
	CUSTOMER INSTALLED CHELSEA 280 SERIES PTO	
	PTO MOUNTING, LH SIDE OF MAIN TRANSMISSION ALLISON	
	MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN	
	HEAVY DUTY ELECTRONIC TRANSMISSION SHIFT CONTROL, COLUMN MOUNTED	

	Description	
	WATER TO OIL TRANSMISSION COOLER	
	TRANSMISSION OIL CHECK AND FILL WITH ELECTRONIC OIL LEVEL CHECK	
	SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)	
Front Axle and Equ	Ipment	
Automotive (Providence) Set (Providence)	DETROIT DA-F-18.0-5 18,000# FL1 71.0 KPI/3.74 DROP SINGLE FRONT AXLE	
	CONMET PRESET PLUS PREMIUM ALUMINUM FRONT HUBS	
	BENDIX ADB22X AIR DISC FRONT BRAKES	
	NON-ASBESTOS FRONT BRAKE LINING	
	BENDIX FRONT DISC SPLINED BRAKE ROTORS	
	NO FRONT BRAKE DUST SHIELDS	
	FRONT OIL SEALS	
	VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL	
	FRONT AIR DISC BRAKE INTERNAL ADJUSTERS	
	DUAL POWER STEERING GEARS, BENDIX 16- 20K	
	4 QUART POWER STEERING RESERVOIR	
	OIL/AIR POWER STEERING COOLER	
	CURRENT AVAILABLE SYNTHETIC 75W-90 FRONT AXLE LUBE	
Front Suspension		
an alay Shara Constant Shara I	20,000# FLAT LEAF FRONT SUSPENSION	n in the second state of the se
	THREADED SPRING PINS AND BUSHINGS - FRONT SUSPENSION	
	AUXILIARY AIR SPRING ON RIGHT SIDE FOR PLOW APPLICATIONS	
	NO FRONT SHOCK ABSORBERS	
Rear Axle and Equip	pment	
and and an an and a start of the second start of	MERITOR MT-40-14X 40,000# R-SERIES TANDEM REAR AXLE	න්තර කරන කලයින්න හර කරන්නයි. ඒ මහේතියෙන් සිංහල්
	CONMET PRESET PLUS PREMIUM ALUMINUM REAR HUBS	
	5.86 REAR AXLE RATIO	
	IRON REAR AXLE CARRIER WITH OPTIONAL HEAVY DUTY AXLE HOUSING	
	MXL 17T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF ROUND YOKES	
	MXL 17T MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH HALF ROUND YOKES	
Application Version 12.0. Data Version PRL-28X.0		10/15/2024 9:26 AM

Data Version PRL-28X.013 Kendall County

	Description
	DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES
	(1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD- REAR AND REAR-REAR AXLE VALVE
	INDICATOR LIGHT FOR EACH INTERAXLE LOCKOUT SWITCH
	INDICATOR LIGHT FOR EACH DIFFERENTIAL LOCKOUT SWITCH
	BENDIX ADB22X AIR DISC REAR BRAKES
	NON-ASBESTOS REAR BRAKE LINING
	BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S)
	REAR DISC BRAKE ROTORS
	REAR BRAKE DUST SHIELDS
	REAR OIL SEALS
	AIR DISC LONGSTROKE 2-DRIVE AXLES SPRING PARKING CHAMBERS
	REAR AIR DISC BRAKE INTERNAL ADJUSTERS
	CURRENT AVAILABLE SYNTHETIC 75W-90 REAR AXLE LUBE
	STANDARD REAR AXLE BREATHER(S)
Rear Suspension	
	TUFTRAC GEN2 40,000# REAR SPRING SUSPENSION
	9.5 INCH NOMINAL RIDE HEIGHT (460MM GLOBAL REFERENCE HEIGHT)
	AXLE CLAMPING GROUP
	55 INCH AXLE SPACING
	FORE/AFT AND TRANSVERSE CONTROL RODS
	REAR SHOCK ABSORBERS - ONE AXLE
Pusher / Tag Equip	ment
	NO PUSHER/TAG BRAKE DUST SHIELDS
Brake System	
	WABCO 6S/4M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH
	REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES
	RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE
	WABCO SYSTEM SAVER HP WITH INTEGRAL AIR GOVERNOR AND HEATER

	Description
8.	WABCO OIL COALESCING FILTER FOR AIR DRYER
	AIR DRYER MOUNTED INBOARD ON LH RAIL
	STEEL AIR TANKS MOUNTED BELOW FRAME RAILS
	PULL CABLE ON WET TANK, PETCOCK DRAIN VALVES ON ALL OTHER AIR TANKS
Trailer Connections	
LERUSELT, MIRELERUSELLEURELEURELEURELEURELEURELEUREL	AIR CONNECTIONS TO END OF FRAME WITH GLAD HANDS FOR TRUCK AND DUST COVERS
	PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, ABS CENTER PIN POWERED THROUGH IGNITION
	SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED END OF FRAME
	NO TRAILER ELECTRICAL CABLE
Wheelbase & Frame	
	4940MM (195 INCH) WHEELBASE, SFA ONLY
	13.0MM X 87.0MM X 311.0MM STEEL FRAME (0.51X3.43X12.24 INCH) 120 KSI
	1900MM (75 INCH) REAR FRAME OVERHANG
	FRAME OVERHANG RANGE: 71 INCH TO 80 INCH
	24 INCH INTEGRAL FRONT FRAME EXTENSION
	CALC'D BACK OF CAB TO REAR SUSP C/L (CA) : 112.99 in
	CALC'D FRAME LENGTH - OVERALL: 321.89 in
	FRAME HEIGHT TOP FRONT UNLADEN : 45.11 in
	FRAME HEIGHT TOP FRONT LADEN : 41.1 in
	FRAME HEIGHT TOP REAR UNLADEN : 43.34 in
	FRAME HEIGHT TOP REAR LADEN : 41.18 in
	SQUARE END OF FRAME
	STANDARD WEIGHT ENGINE CROSSMEMBER
	STANDARD CAST ALUMINUM CROSSMEMBER BACK OF TRANSMISSION
	STANDARD CAST ALUMINUM MIDSHIP
	STANDARD CAST ALUMINUM REARMOST CROSSMEMBER
	STANDARD SUSPENSION CROSSMEMBER
	CAST ALUMINUM REAR SUSPENSION CROSSMEMBER
Chassis Equipment	

10/15/2024 9:26 AM

Page 7 of 14

	Description
5	UNPOLISHED ALUMINUM WST EQUIPMENT COVERS
	PAINTED STEEL 3/16 INCH (7GA) VOCATIONAL BUMPER
	NO FRONT TOW HOOKS
	BUMPER MOUNTING FOR SINGLE LICENSE PLATE
	CLASS 10.9 THREADED METRIC FASTENERS
	EXTERIOR HARNESSES WRAPPED IN ABRASION TAPE
	UPFIT ROUTING AND CLIPPING BRACKET, LH, BOC TO SUSPENSION, UPPER & LOWER SUPPORTS
	UPFIT ROUTING AND CLIPPING BRACKET, RH, BOC TO SUSPENSION, UPPER & LOWER SUPPORTS
Eucl Tanks	
	80 GALLON/302 LITER ALUMINUM FUEL TANK - LH
	25 INCH DIAMETER FUEL TANK(S)
	PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH PAINTED
	BANDS
	FUEL TANK(S) FORWARD
	PLAIN STEP FINISH
	EQUIFLO INBOARD FUEL SYSTEM
	HIGH TEMPERATURE REINFORCED NYLON FUEL LINE
Tires	
	CONTINENTAL HAU 3 WT 315/80R22.5 20 PLY RADIAL FRONT TIRES
	CONTINENTAL INTELLIGENT HDC3 11R22.5 16 PLY RADIAL REAR TIRES
Wheels	
	ALCOA ULTRA ONE 89U63X 22.5X9.00 10-HUB PILOT 3.12 INSET 10-HD ALUMINUM FRONT WHEELS
	ALCOA ULA18X 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS
	FRONT WHEEL MOUNTING NUTS
	REAR WHEEL MOUNTING NUTS
	NYLON WHEEL GUARDS FRONT AND REAR ALL INTERFACES

	tion

Description	
Cab Exterior	
111.6 INCH BBC CONVENTIONAL ALUMINUM CAB	
STAINLESS STEEL CAB ACCENT MOLDING	
FRONT FENDERS	
BOLT-ON MOLDED FLEXIBLE FENDER EXTENSIONS	
INTERIOR GRAB HANDLES WITH ADDED LOWER LH AND RH A PILLAR GRAB HANDLES AND LH AND RH EXTERIOR NON-SLIP GRAB HANDLES	
BRIGHT HOOD MOUNTED AIR INTAKE GRILLE, BLACK SCREEN, WITH LED ACCENT LIGHTS	
X-SERIES STEEL REINFORCED ALUMINUM CAB	
X-SERIES VOCATIONAL HOOD	
HOOD OPENING ASSIST WITH LOCKING STRUT	
WESTERN STAR NAMEPLATES	
SINGLE AIR HORN UNDER LH DECK	
SINGLE ELECTRIC HORN	
REAR LICENSE PLATE MOUNT END OF FRAME	
SWITCH AND WIRING WITH STAINLESS STEEL BRACKETS MOUNTED OUTBOARD ROOF FOR (2) CUSTOMER FURNISHED BEACONS	
DUAL STAGE INTELLIGENT LED HEADLIGHTS WITH HEATED LENS SYSTEM	
VISOR MOUNTED LED MARKER LIGHTS	
WIRING AND SWITCH FOR CUSTOMER FURNISHED SNOW PLOW LAMPS WITH DUAL CONNECTIONS AT BUMPER	
DAYTIME RUNNING LIGHTS	
INDIVIDUAL LED STOP/TURN/BACKUP LIGHTS GROMMET MOUNTED BELOW RAIL	
LED SIDE TURN SIGNAL	
C-BAR MIRROR SYSTEM WITH DUAL HEATED MIRRORS WITH INTEGRAL HEATED CONVEX, DUAL REMOTE, STAINLESS STEEL BACK COVER, AND BLACK C-BAR	
102 INCH EQUIPMENT WIDTH	
LH AND RH CONVEX MIRRORS INTEGRAL WITH PRIMARY MIRRORS	
RH DOWN VIEW MIRROR	
STANDARD SIDE/REAR REFLECTORS	

UNPOLISHED ALUMINUM WST AFTERTREATMENT SYSTEM COVER

Application Version 12.0.009 Data Version PRL-28X.013 Kendall County

Description

NO SLEEPER VENT STAINLESS STEEL EXTERIOR SUN VISOR WITH INTEGRAL MARKER LIGHTS SINGLE SOLAR TINTED REAR WINDOW, (1) 31 INCH X 20 INCH 1-PIECE ROPED-IN SOLAR GREEN GLASS WINDSHIELD 8 LITER (2 GAL) WINDSHIELD WASHER RESERVOIR, CAB MOUNTED, WITH FLUID

LEVEL INDICATOR

Cab Interior

X-SERIES BASE INTERIOR TRIM LEVEL PACKAGE

CHARCOAL BLACK VINYL BASE LEVEL INTERIOR

CARBON WITH BASE BLACK ACCENT

BLACK MATS WITH ADDED FLOOR HEAT AND NOISE INSULATION

(2) DASH MOUNTED POWER OUTLETS AND COIN TRAY

FORWARD ROOF MOUNTED CONSOLE

LH AND RH DOOR STORAGE POCKETS INTEGRATED INTO MOLDED DOOR PANELS

(2) COAT HOOKS ON BACKWALL OF CAB NO UPPER BUNK

DIGITAL ALARM CLOCK IN DRIVER DISPLAY

2-1/2 LB. FIRE EXTINGUISHER SHIPPED LOOSE IN CAB

STANDARD HEATER PLUMBING WITH BALL SHUTOFF VALVES AT SUPPLY LINES ONLY

RADIATOR MOUNTED AIR CONDITIONER CONDENSER

PREMIUM INSULATION

STANDARD LED CAB LIGHTING

NO SECURITY DEVICE

DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME

KEY QUANTITY OF 3

LH AND RH ELECTRIC DOOR LOCKS WITH AUTO UNLOCK FEATURE WHEN DOOR IS SET FROM OPEN TO CLOSED POSITION

BLACK DOOR HANDLES

NO MATTRESS

Application Version 12.0.009 Data Version PRL-28X.013 Kendall County

Description

TRIANGULAR REFLECTORS KIT WITHOUT FLARES SHIPPED LOOSE IN CAB BASIC 2.0 HIGH BACK AIR SUSPENSION DRIVER

SEAT WITH 1 CHAMBER AIR LUMBAR, INTEGRATED CUSHION EXTENSION AND TILT

BATTERY BOX MID BACK NON SUSPENSION PASSENGER SEAT

DUAL DRIVER SEAT ARMRESTS, NO PASSENGER SEAT ARMRESTS

BLACK MORDURA CLOTH DRIVER SEAT COVER WITH EMBROIDERED LOGO

BLACK MORDURA CLOTH PASSENGER SEAT COVER WITH NO LOGO

3 POINT ADJUSTABLE D-RING RETRACTOR DRIVER AND FIXED D-RING RETRACTOR PASSENGER SEAT BELTS

ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN

4-SPOKE 18 INCH (450MM) BLACK STEERING WHEEL WITH SWITCHES

DRIVER AND PASSENGER INTERIOR SUN VISORS

Instruments & Controls

STANDARD FOOT PEDAL SYSTEM

ELECTRONIC ACCELERATOR CONTROL

BLACK GAUGE BEZELS

STANDARD CENTER INSTRUMENT PANEL

DUAL NEEDLE PRIMARY AND SECONDARY AIR PRESSURE GAUGE

INTAKE MOUNTED AIR RESTRICTION INDICATOR WITHOUT GRADUATIONS

ELECTRONIC CRUISE CONTROL WITH CONTROLS ON STEERING WHEEL SPOKES

KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY

PREMIUM INSTRUMENT CLUSTER WITH 5.0 INCH TFT COLOR DISPLAY

PANEL LAMP DIMMER SWITCH IN SWITCH PANEL

HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR WITH DUST CAP LOCATED BELOW LH DASH

2 INCH ELECTRIC FUEL GAUGE

ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE

Application Version 12.0.009 Data Version PRL-28X.013 Kendall County

Description
NO ENGINE OIL TEMPERATURE GAUGE
ELECTRIC ENGINE OIL PRESSURE GAUGE
2 INCH TRANSMISSION OIL TEMPERATURE GAUGE
ELECTRONIC OUTSIDE TEMPERATURE SENSOR DISPLAY IN DRIVER MESSAGE CENTER
ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY
PTO CONTROLS FOR ENHANCED VEHICLE ELECTRIC/ELECTRONIC ARCHITECTURE
NO OBSTACLE DETECTION SYSTEM
NO DR ASSIST SYSTEM
NO VEHICLE STABILITY ADVISOR OR CONTROL
NO LANE DEPARTURE WARNING SYSTEM
TMC RP1226 ACCESSORY CONNECTOR LOCATED BEHIND PASSENGER SIDE REMOVEABLE DASH PANEL
AM/FM/WB WORLD TUNER RADIO WITH BLUETOOTH, USB AND AUXILIARY INPUTS, J1939
DASH MOUNTED RADIO
STANDARD SPEAKER SYSTEM
NO AM/FM RADIO ANTENNA
POWER AND GROUND WIRING PROVISION OVERHEAD
ROOF/OVERHEAD CONSOLE CB RADIO PROVISION
SINGLE REMOTE SPEAKER WITH LEAD FOR 2- WAY RADIO
SINGLE FIBERGLASS LH MIRROR MOUNTED CB ANTENNA WITH BRACKET AND LEAD
HEADLINER MULTI-BAND ANTENNA: AM/FM/WEATHERBAND, WIFI/BLUETOOTH, GNSS/GPS
ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITHOUT ODOMETER
ELECTRONIC 2500 RPM TACHOMETER
DETROIT CONNECT PLATFORM HARDWARE
5 YEARS DAIMLER CONNECTIVITY BASE PACKAGE (FEATURES VARY BY MODEL) POWERED BY DETROIT CONNECT ON CUMMINS ENGINES

-

10/15/2024 9:26 AM

Page 12 of 14

	Description
	NO EXTENSIONS
	IGNITION SWITCH CONTROLLED ENGINE STOP
	NO PRE TRIP SYSTEM TEST
	BW TRACTOR PROTECTION VALVE
	TRAILER HAND CONTROL BRAKE VALVE
	DIGITAL TURBO AIR PRESSURE IN DRIVER DISPLAY
	DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY
	ROTARY HEADLAMP SWITCH, MARKER LIGHTS/HEADLIGHTS SWITCH WITH PULL OUT FOR OPTIONAL FOG/ROAD LAMPS
	TWO VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR
	SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, HEADLAMP FLASH, WASH/WIPE/INTERMITTENT
Design	
	PAINT: ONE SOLID COLOR
Color	
	CAB COLOR A: L6460EY SCHOOL BUS YELLOW ELITE EY
	BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT
	BUMPER PAINTED SAME AS CHASSIS
Certification / Co	ompliance
C TOTAL SECTOR STRUCTURE	U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS

Extended Warranty

CUM 2017 L9: HD1 MD DTY 5 YEARS / 100,000 MILES / 161,000 KM EXTENDED WARRANTY. FEX APPLIES



KENDALL COUNTY HIGHWAY DEPARTMENT

6780 Route 47 Yorkville, Illinois 60560

(630) 553-7616

BID FORM RETURN WITH BID

BID OPENING:	November 8, 2024	10:00 A.M.
BID SUBMITTED BY:	<u> </u>	
	Phone ()	

BID PRICE

Total bid price for new tandem axle cab & chassis as detailed herein: \$_____

Signature of Bidder

Date

Title